

# DEFY ADVANCED E+ ELITE 0

**GIANT**



## SPECS

HYBRID CYCLING TECHNOLOGY	
<b>MOTOR</b>	SyncDriveMove Plus Hub drive 75Nm max
<b>CONTROLLER</b>	Mode support switch from SRAM bonus button
<b>DISPLAY</b>	Giant RideControl GO, frame-integrated LED console Optional wireless ANT+ display
<b>BATTERY</b>	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
<b>CHARGER</b>	Giant EnergyPak 4A smart charger, 60% in 1:45
<b>CONNECTIVITY</b>	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
FRAME	
<b>SIZES</b>	S, M, ML, L, XL
<b>COLORS</b>	Blue Dragonfly / Black
<b>FRAME</b>	Advanced-grade composite, 12x145 thru-axle
<b>FORK</b>	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
<b>SHOCK</b>	-
COMPONENTS	
<b>HANDLEBAR</b>	Giant Contact SLR D-Fuse 31.8 carbon
<b>STEM</b>	Contact SLR Aerolight 31.8 carbon
<b>SEATPOST</b>	Giant D-Fuse SLR, Composite, -5/+15mm offset
<b>SADDLE</b>	Giant Fleet SL
DRIVETRAIN	
<b>SHIFTERS</b>	Sram RED AXS
<b>FRONT DERAILLEUR</b>	Sram RED AXS
<b>REAR DERAILLEUR</b>	Sram RED AXS
<b>BRAKES</b>	Sram RED AXS HRD, Centerline 160mm center-lock [F] 160mm 6-bols [R]
<b>BRAKE LEVERS</b>	Sram RED AXS HRD
<b>CASSETTE</b>	SRAM RED XG-1290 10x33T 12-speed
<b>CHAIN</b>	Sram RED 12-speed
<b>CRANKSET</b>	Sram Force X-SYNC 33/46T BCD107 chain ring Praxis E Crank Carbon ISIS
<b>BOTTOM BRACKET</b>	Giant E+ System BBSS

WHEELS	
<b>RIMS</b>	Giant SLR 1 E+ 36 Carbon Disc Wheel System, Hookless, Tubeless Ready, 12mm thru-axle
<b>SPOKES</b>	Sapim spoke E-Light [R] CX-Ray [F], e-bike optimized
<b>TIRES</b>	Cadex Classic 95PSI 700x28C 170TPI Tubeless Foldable
ACCESSORIES	
<b>LIGHTING</b>	Seatpost clamp integrated tail light

## GEOMETRY

FRAME	S	M	ML	L	XL
Seat Tube Length (mm)	445	480	515	535	565
Seat Tube Angle	74,0°	73,5°	73,0°	73,0°	73,0°
Top Tube Length (mm)	530	545	560	575	590
Head Tube Length (mm)	130	145	167	187	205
Head Tube Angle	71,5°	72,5°	72,5°	72,5°	72,5°
Fork Rake (mm)	50	50	50	50	50
Trail (mm)	65,1	58,6	58,6	58,6	58,6
Wheelbase (mm)	994,3	995,2	1007,5	1022,7	1037,9
Chain Stay Length (mm)	420	420	420	420	420
Bottom Bracket Drop (mm)	80	80	75	75	75
Stack (mm)	542,2	560,2	576,1	595,2	612,4
Reach (mm)	374,3	378,9	383,6	392,8	402,6
Stand Over Height (mm)	716	745,5	779	799	824
Handlebar Width (mm)	400	420	420	440	440
Stem Length (mm)	90	100	110	110	120
Crank Length (mm)	170	172,5	172,5	175	175
Wheel Size	700C	700C	700C	700C	700C

All specifications listed are subject to change without notice.