

DEFY ADVANCED E+ ELITE 0



ŠPECIFIKÁCIE

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDriveMove Plus Hub drive 75Nm max
OVLÁDAČ	Mode support switch from SRAM bonus button
OVLÁDACIA JEDNOTKA	Giant RideControl GO, frame-integrated LED console Optional wireless ANT+ display
BATÉRIA	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
NABÍJAČKA	Giant EnergyPak 4A smart charger, 60% in 1:45
KONEKTIVITA	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
RÁM	
VEĽKOSTI	S, M, ML, L, XL
FARBY	Blue Dragonfly / Black
RÁM	Advanced-grade composite,12x145 thru-axle
VIDLICA	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
TLMIČ	-
KOMPONENTY	
RIADIDLÁ	Giant Contact SLR D-Fuse 31.8 carbon
PREDSTAVEC	Contact SLR Aerolight 31.8 carbon
SEDLOVKA	Giant D-Fuse SLR, Composite, -5/+15mm offset
SEDADLO	Giant Fleet SL
POHON	
RADENIE	Sram RED AXS
PREŠMYKAČ	Sram RED AXS
PREHADZOVAČKA	Sram RED AXS
BRZDY	Sram RED AXS HRD, Centerline 160mm center-lock [F] 160mm 6-bols [R]
BRZDOVÉ PÁKY	Sram RED AXS HRD
KAZETA	SRAM RED XG-1290 10x33T 12-speed
REŤAZ	Sram RED 12-speed
KLUKY	Sram Force X-SYNC 33/46T BCD107 chain ring Praxis E Crank Carbon ISIS
STREDOVÉ ZLOŽENIE	Giant E+ System BBSS

KOLESÁ	
RÁFIKY	Giant SLR 1 E+ 36 Carbon Disc Wheel System, Hookless, Tubeless Ready, 12mm thru-axle
ŠPICE	Sapim spoke E-Light [R] CX-Ray [F], e-bike optimized
PNEUMATIKY	Cadex Classic 95PSI 700x28C 170TPI Tubeless Foldable
PRÍSLUŠENSTVO	
OSVETLENIE	Seatpost clamp integrated tail light

Cena: 10 999 €

GEOMETRIA

RÁM	S	M	ML	L	XL
Dĺžka sedlovej trubky (mm)	445	480	515	535	565
Uhol sedlovej trubky	74,0°	73,5°	73,0°	73,0°	73,0°
Dĺžka hornej rámovej trubky (mm)	530	545	560	575	590
Dĺžka hlavovej trubky (mm)	130	145	167	187	205
Uhol hlavovej trubky	71,5°	72,5°	72,5°	72,5°	72,5°
Offset vidlice (mm)	50	50	50	50	50
Trail (mm)	65,1	58,6	58,6	58,6	58,6
Rázvor (mm)	994,3	995,2	1007,5	1022,7	1037,9
Dĺžka zadnej stavby (mm)	420	420	420	420	420
Rozdiel zadnej voči stredovej osi - BB DROP (mm)	80	80	75	75	75
Stack - výška riadenia (mm)	542,2	560,2	576,1	595,2	612,4
Reach (mm)	374,3	378,9	383,6	392,8	402,6
Výška rámu od zeme (mm)	716	745,5	779	799	824
Šírka riaditok (mm)	400	420	420	440	440
Dĺžka predstavca (mm)	90	100	110	110	120
Dĺžka kľúk (mm)	170	172,5	172,5	175	175
Rozmer kolies	700C	700C	700C	700C	700C

Všetky ceny a špecifikácie sa môžu zmeniť bez predchádzajúceho upozornenia.