

DEFY ADVANCED E+ ELITE 0

GIANT



SPECS

HYBRID CYKELTEKNIK	
MOTOR	SyncDriveMove Plus Hub drive 75Nm max
KONTROLLER	Mode support switch from SRAM bonus button
VISA	Giant RideControl GO, frame-integrated LED console Optional wireless ANT+ display
BATTERI	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
LADDARE	Giant EnergyPak smart charger 4A
CONNECTIVITY	Giant RideControl App enabled, ANT+ wireless display signal with e-bike profile
RAM	
STORLEKAR	S, M, ML, L, XL
FÄRGER	Midnight Moon
RAM	Advanced-grade composite, 12x145 thru-axle
GAFFEL	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
BAKDÄMPARE	-
KOMPONENTER	
STYRE	Giant Contact SLR D-Fuse 31.8 carbon
STAM	Contact SLR Aerolight 31.8 carbon
SADELSTOLPE	Giant D-Fuse SLR, Composite, -5/+15mm offset
SADEL	Giant Fleet SL
DRIVLINJA	
VÄXLAR	Sram RED AXS
FRAMVÄXEL	Sram RED AXS
BAKVÄXEL	Sram RED AXS
BROMSAR	Sram RED AXS HRD, Centerline 160mm center-lock [F] 160mm 6-bols [R]
BROMSSPAKAR	Sram RED AXS HRD
KASSETT	SRAM RED XG-1290 10x33T 12-speed
KEDJA	Sram RED 12-speed
VEVPARTI	Sram Force X-SYNC 33/46T BCD107 chain ring Praxis E Crank Carbon ISIS
BROMSREGLAGE	Giant E+ System BBSS

HJUL	
FÄLGAR	Giant SLR 1 E+ 36 Carbon Disc Wheel System, Hookless, Tubeless Ready, 12mm thru-axle, w/ Sapim spoke E-Light [R] CX-Ray [F], e-bike optimized
DÄCK	Cadex Race GC, tubeless, 700x30, folding
EXTRAFUNKTIONER	Fender adapter
TILLBEHÖR	
BELYSNING	Seatpost clamp integrated tail light

Price: 126 990,00 kr

GEOMETRY

RAM	S	M	ML	L	XL
Längd sadelrör (mm)	445	480	515	535	565
Vinkel sadelrör	74,0°	73,5°	73,0°	73,0°	73,0°
Topprörets längd (mm)	530	545	560	575	590
Styrhuvud Längd (mm)	130	145	167	187	205
Vinkel styrhuvud	71,5°	72,5°	72,5°	72,5°	72,5°
Gaffelvinkel (mm)	50	50	50	50	50
Hjulbas (mm)	994	995	1008	1023	1037,9
Kedjestagslängd (mm)	420	420	420	420	420
Nedre fäste Drop (mm)	80	80	75	75	75
Stack (mm)	542	560	576	595	612,4
Reach (mm)	374	379	384	393	402,6
Stå över höjden (mm)	716	746	779	799	824
Styrets bredd (mm)	400	420	420	440	440
Stamlängd (mm)	90	100	110	110	120
Hjulstorlek	700C	700C	700C	700C	700C

All specifications listed are subject to change without notice.