

DEFY ADVANCED E+ ELITE 0



СПЕЦИФІКАЦІЯ

ТЕХНОЛОГІЯ HYBRID CYCLING	
ДВИГУН	SyncDriveMove Plus Hub drive 75Nm max
КОНТРОЛЕР	Mode support switch from SRAM bonus button
ДИСПЛЕЙ	Giant RideControl GO, frame-integrated LED console Optional wireless ANT+ display
БАТАРЕЯ	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
CHARGER	Giant EnergyPak 4A smart charger, 60% in 1:45
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
РАМА	
РОЗМІР	S, M, ML, L, XL
КОЛІР	Blue Dragonfly / Black
КОНСТРУКЦІЯ	Advanced-grade composite,12x145 thru-axle
ВИЛКА	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
АМОРТИЗАТОР ЗАДНІЙ	-
КОМПОНЕНТИ	
КЕРМО	Giant Contact SLR D-Fuse 31.8 carbon
ВИНОС КЕРМА	Contact SLR Aerolight 31.8 carbon
ВИНОС СІДЛА	Giant D-Fuse SLR, Composite, -5/+15mm offset
СІДЛО	Giant Fleet SL
ПРИВІД	
МАНЕТКИ	Sram RED AXS
ПЕРЕМИКАЧ ПЕРЕДНІЙ	Sram RED AXS
ПЕРЕМИКАЧ ЗАДНІЙ	Sram RED AXS
ГАЛЬМА	Sram RED AXS HRD, Centerline 160mm center-lock [F] 160mm 6-bols [R]
ВАЖЕЛІ ГАЛЬМ	Sram RED AXS HRD
КАСЕТА	SRAM RED XG-1290 10x33T 12-speed
ЛАНЦЮГ	Sram RED 12-speed
СИСТЕМА ШАТУНІВ	Sram Force X-SYNC 33/46T BCD107 chain ring Praxis E Crank Carbon ISIS
КАРЕТКА	Giant E+ System BBSS

КОЛЕСА	
ОБОДИ	Giant SLR 1 E+ 36 Carbon Disc Wheel System, Hookless, Tubeless Ready, 12mm thru-axle
СПИЦІ	Sapim spoke E-Light [R] CX-Ray [F], e-bike optimized
ШИНИ	Cadex Classic 95PSI 700x28C 170TPI Tubeless Foldable
АКСЕСУАРИ	
ОСВІТЛЕННЯ	Seatpost clamp integrated tail light

ГЕОМЕТРІЯ

РАМА	S	M	ML	L	XL
Довжина підсідельної труби (mm)	445	480	515	535	565
Нахил підсідельної труби	74,0°	73,5°	73,0°	73,0°	73,0°
Довжина верхньої труби (mm)	530	545	560	575	590
Висота кермової труби (mm)	130	145	167	187	205
Нахил кермової труби	71,5°	72,5°	72,5°	72,5°	72,5°
Виліт вилки (mm)	50	50	50	50	50
Шлях вилки (mm)	65,1	58,6	58,6	58,6	58,6
Колісна база (mm)	994,3	995,2	1007,5	1022,7	1037,9
Довжина нижніх пір'їв рами (mm)	420	420	420	420	420
Провисання каретки (mm)	80	80	75	75	75
Ефективна висота (mm)	542,2	560,2	576,1	595,2	612,4
Ефективна довжина (mm)	374,3	378,9	383,6	392,8	402,6
Безпечна висота (mm)	716	745,5	779	799	824
Ширина керма (mm)	400	420	420	440	440
Довжина виносу (mm)	90	100	110	110	120
Довжина шатунів (mm)	170	172,5	172,5	175	175
Розмір коліс	700C	700C	700C	700C	700C

Giant залишає за собою право змінювати специфікації без попереднього повідомлення.