

DEFY ADVANCED E+ ELITE 1

GIANT



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDriveMove Plus Hub drive 75Nm max
CONTROLLER	Mode support switch from SRAM bonus button
DISPLAY	Giant RideControl GO, frame-integrated LED console Optional wireless ANT+ display
BATTERY	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
CHARGER	Giant EnergyPak smart charger 4A
CONNECTIVITY	Giant RideControl App enabled, ANT+ wireless display signal with e-bike profile
ΣΚΕΛΕΤΟΣ	
ΜΕΓΕΘΗ	S, M, ML, L, XL
ΧΡΩΜΑΤΑ	Mariana Blue
ΣΚΕΛΕΤΟΣ	Advanced-grade composite, 12x145 thru-axle
ΠΙΡΟΥΝΙ	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
ΕΞΑΡΤΗΜΑΤΑ	
ΤΙΜΟΝΙ	Giant Contact SLR D-Fuse 31.8 carbon
ΛΑΙΜΟΣ ΤΙΜΟΝΙΟΥ	Contact SLR Aerolight 31.8 carbon
ΛΑΙΜΟΣ ΣΕΛΛΑΣ	Giant D-Fuse SL, Composite, 16mm offset
ΣΕΛΛΑ	Giant Fleet SL
ΜΕΤΑΔΟΣΗ	
ΛΕΒΙΕ ΤΑΧΥΤΗΤΩΝ	Sram Force AXS
ΝΤΕΡΑΓΓΙΕΡ ΕΜΠΡΟΣΘΙΟ	Sram Force AXS
ΝΤΕΡΑΓΓΙΕΡ ΟΠΙΣΘΙΟ	Sram Force AXS
ΦΡΕΝΑ	Sram Force AXS HRD, Centerline 160mm center-lock [F] 160mm 6-bols [R]
ΜΑΝΕΤΤΕΣ ΦΡΕΝΩΝ	Sram Force AXS HRD
CASETTE Η ΕΛΕΥΘΕΡΟ	SRAM Force XG-1270 10x33T 12-speed
ΑΛΥΣΙΔΑ	Sram Force 12-speed
ΔΙΣΚΟΒΡΑΧΙΩΝΑΣ	Sram Force X-SYNC 33/46T BCD107 chain ring Praxis E Crank Carbon ISIS
BOTTOM BRACKET	Giant E+ System BBSS

WHEELS	
ΣΤΕΦΑΝΙΑ	Giant SLR 1 E+ 36 Carbon Disc Wheel System, Hookless, Tubeless Ready, 12mm thru-axle, w/ Sapim spoke E-Light [R] CX-Ray [F], e-bike optimized
ΕΛΑΣΤΙΚΑ	Cadex Classic, tubeless, 700x32, folding
EXTRAS	Fender adapter
ACCESSORIES	
LIGHTING	Seatpost clamp integrated tail light

ΓΕΩΜΕΤΡΙΑ

ΣΚΕΛΕΤΟΣ	S	M	ML	L	XL
Seat Tube Length (mm)	445	480	515	535	565
Seat Tube Angle	74,0°	73,5°	73,0°	73,0°	73,0°
Top Tube Length (mm)	530	545	560	575	590
Head Tube Length (mm)	130	145	167	187	205
Head Tube Angle	71,5°	72,5°	72,5°	72,5°	72,5°
Fork Rake (mm)	50	50	50	50	50
Trail (mm)	56,1	58,6	58,6	58,6	58,6
Wheelbase (mm)	994	995	1008	1023	1037,9
Chain Stay Length (mm)	420	420	420	420	420
Bottom Bracket Drop (mm)	80	80	75	75	75
Stack (mm)	542	560	576	595	612,4
Reach (mm)	374	379	384	393	402,6
Stand Over Height (mm)	716	746	779	799	824
Handlebar Width (mm)	400	420	420	440	440
Stem Length (mm)	90	100	110	110	120
Wheel Size	700C	700C	700C	700C	700C

Όλες οι προδιαγραφές είναι δυνατό να αλλάξουν χωρίς πρότερη ειδοποίηση