

# DEFY ADVANCED E+ ELITE 1



## SPECS

HYBRID CYCLING TECHNOLOGY	
<b>MOTOR</b>	Giant SyncDrive Move Plus, Rear Hub, 30Nm
<b>CONTROLLER</b>	Mode support switch from SRAM blips
<b>DISPLAY</b>	RideControl GO, frame integrated LED display ANT+ Wireless display compatible
<b>BATTERY</b>	EnergyPak Smart 400Wh EnergyPak Plus, range extender compatible
<b>CHARGER</b>	EnergyPak 4A smart charger compact
<b>MAXIMUM ASSISTED SPEED</b>	Pedal-assist limited to 25 km/h in accordance with Australian regulations (EN15194); no motor support above this speed
<b>CONNECTIVITY</b>	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
FRAME	
<b>SIZES</b>	S, M, M/L, L, XL
<b>COLOURS</b>	Raw Carbon
<b>FRAME</b>	Advanced-Grade Composite, disc, 12x145mm
<b>FORK</b>	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, disc, 12x100mm
<b>SHOCK</b>	-
COMPONENTS	
<b>HANDLEBAR</b>	Giant Contact SLR D-Fuse S:40/42cm, M:42/44cm, M/L:42/44cm, L:44/46cm, XL:44/46cm
<b>GRIPS</b>	Stratus Lite 3.0
<b>STEM</b>	Giant Contact SLR AeroLight S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
<b>SEATPOST</b>	Giant D-Fuse SL, composite, -5/+15mm offset
<b>SADDLE</b>	Giant Fleet SL
<b>PEDALS</b>	N/A
DRIVETRAIN	
<b>SHIFTERS</b>	SRAM Force AXS
<b>FRONT DERAILLEUR</b>	SRAM Force AXS
<b>REAR DERAILLEUR</b>	SRAM Force AXS
<b>BRAKES</b>	SRAM Force AXS hydraulic, SRAM CenterLine X rotors [F]160mm, [R]160mm
<b>BRAKE LEVERS</b>	SRAM Force AXS hydraulic
<b>CASSETTE</b>	SRAM Force XG-1270, 12-speed, 10-33
<b>CHAIN</b>	SRAM Force D1
<b>CRANKSET</b>	SRAM Force X-SYNC 33/46T BCD107 chain ring Praxis E Crank Carbon ISIS, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
<b>BOTTOM BRACKET</b>	Giant E+ System BBSS

WHEELS	
<b>RIMS</b>	Giant SLR 1 E+ 36mm Carbon Disc Wheel System, Hookless, Tubeless Ready
<b>HUBS</b>	[F] Giant SLR 1, 24H [R] Giant SyncDrive Move Plus, 28H
<b>SPOKES</b>	Sapim spoke E-Light [R] CX-Ray [F], e-bike optimised
<b>TYRES</b>	CADEX Classics, tubeless, 700x32c, folding
ACCESSORIES	
<b>LIGHTING</b>	Seatpost clamp integrated tail light
LIMITS	
<b>MAX TYRE CLEARANCE</b>	38mm

**Price: \$13,499.00**

## GEOMETRY

FRAME	S	M	ML	L	XL
Seat Tube Length (mm)	445	480	515	535	565
Seat Tube Angle	74.0°	73.5°	73.0°	73.0°	73.0°
Top Tube Length (mm)	530	545	560	575	590
Head Tube Length (mm)	130	145	167	187	205
Head Tube Angle	71.5°	72.5°	72.5°	72.5°	72.5°
Fork Rake (mm)	50	50	50	50	50
Trail (mm)	65.1	58.6	58.6	58.6	58.6
Wheelbase (mm)	994.3	995.2	1007.5	1022.7	1037.9
Chain Stay Length (mm)	420	420	420	420	420
Bottom Bracket Drop (mm)	80	80	75	75	75
Stack (mm)	542.2	560.2	576.1	595.2	612.4
Reach (mm)	374.3	378.9	383.6	392.8	402.6
Stand Over Height (mm)	716	745.5	779	799	824
Stem Length (mm)	90	100	110	110	120
Crank Length (mm)	170	172.5	172.5	175	175
Wheel Size	700C	700C	700C	700C	700C

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. \*Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.