

# DEFY ADVANCED E+ ELITE 1

**GIANT**



## SPECS

HYBRID CYCLING TECHNOLOGY	
<b>MOTOR</b>	Giant SyncDrive Move Plus, Rear Hub, 30Nm
<b>CONTROLLER</b>	Mode support switch from SRAM bonus button
<b>DISPLAY</b>	Giant RideControl GO, frame-integrated LED console Optional wireless ANT+ display
<b>BATTERY</b>	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
<b>CHARGER</b>	Giant EnergyPak smart charger 4A
<b>MAXIMUM ASSISTED SPEED</b>	Pedal-assist limited to 25 km/h in accordance with Australian regulations (EN15194); no motor support above this speed
<b>CONNECTIVITY</b>	Giant RideControl App enabled, ANT+ wireless display signal with e-bike profile
FRAME	
<b>SIZES</b>	S, M, ML, L, XL
<b>COLOURS</b>	Meteor Storm
<b>FRAME</b>	Advanced-grade composite, 12x145 thru-axle
<b>FORK</b>	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
COMPONENTS	
<b>HANDLEBAR</b>	Giant Contact SLR D-Fuse S:38/40cm, M:40/42cm, ML:40/42cm, L:42/44cm, XL:42/44cm
<b>STEM</b>	Giant Contact SLR AeroLight S:90mm, M:100mm, ML:110mm, L:110mm, XL:120mm
<b>SEATPOST</b>	Giant D-Fuse SL, Composite, 16mm offset
<b>SADDLE</b>	Giant Fleet SL
<b>PEDALS</b>	N/A
DRIVETRAIN	
<b>SHIFTERS</b>	SRAM Force AXS HRD, ED-Force-E1
<b>FRONT DERAILLEUR</b>	SRAM Force AXS, FD-Force-E-E1
<b>REAR DERAILLEUR</b>	SRAM Force AXS, RD-Force-E-E1
<b>BRAKES</b>	SRAM Force AXS HRD, ED-Force-E1, SRAM PaceLine X rotors [F]160mm, [R]160mm
<b>BRAKE LEVERS</b>	SRAM Force AXS HRD, ED-Force-E1
<b>CASSETTE</b>	SRAM Force XG-1270 10x33T 12-speed
<b>CHAIN</b>	SRAM Force-E1, 12-speed
<b>CRANKSET</b>	SRAM Force X-SYNC 33/46T BCD107 chain ring Praxis E Crank Carbon ISIS, S:170mm, M:172.5mm, ML:172.5mm, L:175mm, XL:175mm
<b>BOTTOM BRACKET</b>	Giant E+ System BBSS

WHEELS	
<b>RIMS</b>	Giant SLR 1 E+ 36 Carbon Disc Wheel System, Hookless, Tubeless Ready, 12mm thru-axle, w/ Sapim spoke E-Light [R] CX-Ray [F], e-bike optimized
<b>TYRES</b>	Cadex Classic, tubeless, 700x32, folding
<b>EXTRAS</b>	N/A
ACCESSORIES	
<b>LIGHTING</b>	Seatpost clamp integrated tail light
LIMITS	
<b>MAX TYRE CLEARANCE</b>	38mm

**Price: \$13,499.00**

## GEOMETRY

FRAME	S	M	ML	L	XL
Seat Tube Length (mm)	445	480	515	535	565
Seat Tube Angle	74.0°	73.5°	73.0°	73.0°	73.0°
Top Tube Length (mm)	530	545	560	575	590
Head Tube Length (mm)	130	145	167	187	205
Head Tube Angle	71.5°	72.5°	72.5°	72.5°	72.5°
Fork Rake (mm)	50	50	50	50	50
Trail (mm)	56.1	58.6	58.6	58.6	58.6
Wheelbase (mm)	994	995	1008	1023	1037.9
Chain Stay Length (mm)	420	420	420	420	420
Bottom Bracket Drop (mm)	80	80	75	75	75
Stack (mm)	542	560	576	595	612.4
Reach (mm)	374	379	384	393	402.6
Stand Over Height (mm)	716	746	779	799	824
Stem Length (mm)	90	100	110	110	120
Wheel Size	700C	700C	700C	700C	700C

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. \*Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.