

DEFY ADVANCED E+ ELITE 1



SPECS

HYBRID CYCLING TECHNOLOGY (PEDAL ASSIST)

MOTOR	SyncDriveMove Plus Hub drive 75Nm max
CONTROLLER	Mode support switch from SRAM Blips
DISPLAY	Giant RideControl GO, frame-integrated LED console Optional wireless ANT+ display
BATTERY	EnergyPak Smart 400Wh by Panasonic, Aluminium casing with highest safety standard (UL2271, EN50604), CO2 Neutral production, 2300 charging cycles. EnergyPak Plus 200 range extender compatible
CHARGER	Giant EnergyPak 4A smart charger, 60% in 1:45
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile

FRAME

SIZES	S, M, ML, L
COLOURS	Gloss Raw carbon / Black
FRAME	Advanced-grade composite, 12x145 thru-axle
FORK	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
SHOCK	-

COMPONENTS

HANDLEBAR	Giant Contact SLR D-Fuse 31.8 carbon
STEM	Contact SLR Aerolight 31.8 carbon
SEATPOST	Giant D-Fuse SL, Composite, 16mm offset
SADDLE	Giant Fleet SL
PEDALS	PEDALS NOT SUPPLIED

DRIVETRAIN

SHIFTERS	Sram Force eTap AXS 2x12
FRONT DERAILLEUR	Sram Force AXS
REAR DERAILLEUR	Sram Force AXS
BRAKES	Sram Force AXS HRD, Centerline 160mm center-lock [F] 160mm 6-bols [R]
BRAKE LEVERS	Sram Force AXS HRD
CASSETTE	SRAM Force XG-1270 10x33T 12-speed
CHAIN	Sram Force 12-speed
CRANKSET	Sram Force X-SYNC 33/46T BCD107 chain ring Praxis E Crank Carbon ISIS
BOTTOM BRACKET	Giant E+ System BBSS

WHEELS

RIMS	Giant SLR 1 E+ 36 Carbon Disc Wheel System, Hookless, Tubeless Ready, 12mm thru-axle, w/ Sapim spoke E-Light [R] CX-Ray [F], e-bike optimised
SPOKES	Sapim spoke E-Light [R] CX-Ray [F], e-bike optimised
TYRES	Cadex Classic 75PSI 700x32C 170TPI Tubeless Foldable

ACCESSORIES

LIGHTING	Seatpost clamp integrated tail light
-----------------	--------------------------------------

Price: £7,999.00

GEOMETRY

FRAME	S	M	ML	L
Seat Tube Length (mm)	445	480	515	535
Seat Tube Angle	74.0°	73.5°	73.0°	73.0°
Top Tube Length (mm)	530	545	560	575
Head Tube Length (mm)	130	145	167	187
Head Tube Angle	71.5°	72.5°	72.5°	72.5°
Fork Rake (mm)	50	50	50	50
Trail (mm)	65.1	58.6	58.6	58.6
Wheelbase (mm)	994.3	995.2	1007.5	1022.7
Chain Stay Length (mm)	420	420	420	420
Bottom Bracket Drop (mm)	80	80	75	75
Stack (mm)	542.2	560.2	576.1	595.2
Reach (mm)	374.3	378.9	383.6	392.8
Stand Over Height (mm)	716	745.5	779	799
Handlebar Width (mm)	400	420	420	440
Stem Length (mm)	90	100	110	110
Crank Length (mm)	170	172.5	172.5	175
Wheel Size	700C	700C	700C	700C

Every effort has been made to ensure accuracy throughout this website. However, Giant reserves the right to change bike specifications, features, prices and colours without prior notice.