

DEFY ADVANCED E+ ELITE 1



SPECS

HYBRID CYCLING TECHNOLOGY

| | |
|---------------------|--|
| MOTOR | SyncDriveMove Plus Hub drive 75Nm max |
| CONTROLLER | Mode support switch from SRAM bonus button |
| DISPLAY | Giant RideControl GO, frame-integrated LED console Optional wireless ANT+ display |
| BATTERY | Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible |
| CHARGER | Giant EnergyPak smart charger 4A |
| CONNECTIVITY | Giant RideControl App enabled, ANT+ wireless display signal with e-bike profile |

FRAME

| | |
|---------------|--|
| SIZES | S, M, ML, L, XL |
| COLORS | Mariana Blue |
| FRAME | Advanced-grade composite, 12x145 thru-axle |
| FORK | Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc |

COMPONENTS

| | |
|-------------------------|---|
| HANDLEBAR | Giant Contact SLR D-Fuse 31.8 carbon |
| STEM | Contact SLR Aerolight 31.8 carbon |
| SEATPOST | Giant D-Fuse SL, Composite, 16mm offset |
| SADDLE | Giant Fleet SL |
| DRIVETRAIN | |
| SHIFTERS | Sram Force AXS |
| FRONT DERAILLEUR | Sram Force AXS |
| REAR DERAILLEUR | Sram Force AXS |
| BRAKES | Sram Force AXS HRD, Centerline 160mm center-lock [F] 160mm 6-bols [R] |
| BRAKE LEVERS | Sram Force AXS HRD |
| CASSETTE | SRAM Force XG-1270 10x33T 12-speed |
| CHAIN | Sram Force 12-speed |
| CRANKSET | Sram Force X-SYNC 33/46T BCD107 chain ring Praxis E Crank Carbon ISIS |
| BOTTOM BRACKET | Giant E+ System BBSS |

WHEELS

| | |
|---------------|---|
| RIMS | Giant SLR 1 E+ 36 Carbon Disc Wheel System, Hookless, Tubeless Ready, 12mm thru-axle, w/ Sapim spoke E-Light [R] CX-Ray [F], e-bike optimized |
| TIRES | Cadex Classic, tubeless, 700x32, folding |
| EXTRAS | Fender adapter |

ACCESSORIES

| | |
|-----------------|--------------------------------------|
| LIGHTING | Seatpost clamp integrated tail light |
|-----------------|--------------------------------------|

Recommended Retail Price: \$9,900.00

GEOMETRY

| FRAME | S | M | ML | L | XL |
|----------------------------|-------|-------|-------|-------|-------|
| Seat Tube Length (inch) | 17.5 | 18.9 | 20.3 | 21.1 | 22.2 |
| Seat Tube Angle | 74.0° | 73.5° | 73.0° | 73.0° | 73.0° |
| Top Tube Length (inch) | 20.9 | 21.5 | 22 | 22.6 | 23.2 |
| Head Tube Length (inch) | 5.1 | 5.7 | 6.6 | 7.4 | 8.1 |
| Head Tube Angle | 71.5° | 72.5° | 72.5° | 72.5° | 72.5° |
| Fork Rake (inch) | 2 | 2 | 2 | 2 | 2 |
| Trail (inch) | 2.2 | 2.3 | 2.3 | 2.3 | 2.3 |
| Wheelbase (inch) | 39.1 | 39.2 | 39.7 | 40.3 | 40.8 |
| Chain Stay Length (inch) | 16.5 | 16.5 | 16.5 | 16.5 | 16.5 |
| Bottom Bracket Drop (inch) | 3.1 | 3.1 | 3 | 3 | 3 |
| Stack (inch) | 21.3 | 22 | 22.7 | 23.4 | 24.1 |
| Reach (inch) | 14.7 | 14.9 | 15.1 | 15.5 | 15.8 |
| Stand Over Height (inch) | 28.2 | 29.4 | 30.7 | 31.5 | 32.4 |
| Handlebar Width (inch) | 15.7 | 16.5 | 16.5 | 17.3 | 17.3 |
| Stem Length (inch) | 3.5 | 3.9 | 4.3 | 4.3 | 4.7 |
| Wheel Size | 700C | 700C | 700C | 700C | 700C |

**All specifications and prices listed are subject to change without notice. Actual weight may vary due to manufacturing tolerances, color variations, frame size and variability in production components.*