

DEFY ADVANCED E+ ELITE 1

GIANT



SPECS

HYBRID CYCLING TECHNOLOGY

MOTOR	SyncDriveMove Plus Hub drive 75Nm max
CONTROLLER	Mode support switch from SRAM bonus button
DISPLAY	Giant RideControl GO, frame-integrated LED console Optional wireless ANT+ display
BATTERY	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
CHARGER	Giant EnergyPak smart charger 4A
CONNECTIVITY	Giant RideControl App enabled, ANT+ wireless display signal with e-bike profile

FRAME

SIZES	S, M, ML, L, XL
COLORS	Mariana Blue
FRAME	Advanced-grade composite, 12x145 thru-axle
FORK	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc

COMPONENTS

HANDLEBAR	Giant Contact SLR D-Fuse 31.8 carbon
STEM	Contact SLR Aerolight 31.8 carbon
SEATPOST	Giant D-Fuse SL, Composite, 16mm offset
SADDLE	Giant Fleet SL
DRIVETRAIN	
SHIFTERS	Sram Force AXS
FRONT DERAILLEUR	Sram Force AXS
REAR DERAILLEUR	Sram Force AXS
BRAKES	Sram Force AXS HRD, Centerline 160mm center-lock [F] 160mm 6-bols [R]
BRAKE LEVERS	Sram Force AXS HRD
CASSETTE	SRAM Force XG-1270 10x33T 12-speed
CHAIN	Sram Force 12-speed
CRANKSET	Sram Force X-SYNC 33/46T BCD107 chain ring Praxis E Crank Carbon ISIS
BOTTOM BRACKET	Giant E+ System BBSS

WHEELS

RIMS	Giant SLR 1 E+ 36 Carbon Disc Wheel System, Hookless, Tubeless Ready, 12mm thru-axle, w/ Sapim spoke E-Light [R] CX-Ray [F], e-bike optimized
TIRES	Cadex Classic, tubeless, 700x32, folding
EXTRAS	Fender adapter

ACCESSORIES

LIGHTING	Seatpost clamp integrated tail light
-----------------	--------------------------------------

GEOMETRY

FRAME	S	M	ML	L	XL
Seat Tube Length (mm)	445	480	515	535	565
Seat Tube Angle	74,0°	73,5°	73,0°	73,0°	73,0°
Top Tube Length (mm)	530	545	560	575	590
Head Tube Length (mm)	130	145	167	187	205
Head Tube Angle	71,5°	72,5°	72,5°	72,5°	72,5°
Fork Rake (mm)	50	50	50	50	50
Trail (mm)	56,1	58,6	58,6	58,6	58,6
Wheelbase (mm)	994	995	1008	1023	1037,9
Chain Stay Length (mm)	420	420	420	420	420
Bottom Bracket Drop (mm)	80	80	75	75	75
Stack (mm)	542	560	576	595	612,4
Reach (mm)	374	379	384	393	402,6
Stand Over Height (mm)	716	746	779	799	824
Handlebar Width (mm)	400	420	420	440	440
Stem Length (mm)	90	100	110	110	120
Wheel Size	700C	700C	700C	700C	700C

All specifications listed are subject to change without notice.