DEFY ADVANCED E+ ELITE 1



SPECS

TECNOLOGIA HÍBRIDA DE CICLISMO	
MOTOR	SyncDriveMove Plus Hub drive 75Nm max
SENSOR	Mode support switch from SRAM Blips
ECRÃ	Giant RideControl GO, frame-integrated LED console Optional wireless ANT+ display
BATERIA	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
CARREGADOR	Giant EnergyPak 4A smart charger, 60% in 1:45
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
QUADRO	
TAMANHOS	S, M, ML, L, XL
CORES	Raw carbon / Black
QUADRO	Advanced-grade composite,12x145 thru-axle
FORQUILHA	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
AMORTECEDORES	-
COMPONENTES	
GUIADOR	Giant Contact SLR D-Fuse 31.8 carbon
AVANÇO	Contact SLR Aerolight 31.8 carbon
ESPIGÃO DE SELIM	Giant D-Fuse SL, Composite, 16mm offset
SELIM	Giant Fleet SL
TRANSMISSÃO	
MANETES	Sram Force AXS
DESVIADOR DIANTEIRO	Sram Force AXS
DESVIADOR TRASEIRO	Sram Force AXS
TRAVÕES	Sram Force AXS HRD, Centerline 160mm center-lock [F] 160mm 6-bols [R]
MANÍPULOS DOS TRAVÕES	Sram Force AXS HRD
CASSETE	SRAM Force XG-1270 10x33T 12-speed
CORRENTE	Sram Force 12-speed
CONJUNTO PEDALEIRO	Sram Force X-SYNC 33/46T BCD107 chain ring Praxis E Crank Carbon ISIS
MOVIMENTO CENTRAL	Giant E+ System BBSS

RODAS	
AROS	Giant SLR 1 E+ 36 Carbon Disc Wheel System, Hookless, Tubeless Ready, 12mm thru-axle
RAIOS	Sapim spoke E-Light [R] CX-Ray [F], e-bike optimized
PNEUS	Cadex Classic 75PSI 700x32C 170TPI Tubeless Foldable
ACESSÓRIOS	
LUZES	Seatpost clamp integrated tail light

Preço: 6 999,00 €

GEOMETRIA

QUADRO	S	M	ML	L	XL
Comprimento do tubo do assento (mm)	445	480	515	535	565
Ângulo do tubo do assento	74,0°	73,5°	73,0°	73,0°	73,0°
Comprimento do tubo superior (mm)	530	545	560	575	590
Comprimento do tubo principal (mm)	130	145	167	187	205
Ângulo do tubo principal	71,5°	72,5°	72,5°	72,5°	72,5°
Garfo ancinho (mm)	50	50	50	50	50
Trilha (mm)	65,1	58,6	58,6	58,6	58,6
distância entre eixos (mm)	994,3	995,2	1007,5	1022,7	1037,9
Comprimento Chain Stay (mm)	420	420	420	420	420
Suporte inferior (mm)	80	80	75	75	75
Pilha (mm)	542,2	560,2	576,1	595,2	612,4
Alcançar (mm)	374,3	378,9	383,6	392,8	402,6
Altura do standover (mm)	716	745,5	779	799	824
Largura do guidão (mm)	400	420	420	440	440
Comprimento da haste (mm)	90	100	110	110	120
Comprimento da Manivela (mm)	170	172,5	172,5	175	175
Tamanho da roda	700C	700C	700C	700C	700C

Todas as especificações apresentadas estão sujeitas a alterações sem aviso prévio.