

# DEFY ADVANCED E+ ELITE 2

GIANT



## SPECIFIKATIONER

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDriveMove Plus Hub drive 75Nm max
KONTROLLER	Mode support switch from SRAM Blips
DISPLAY	Giant RideControl GO, frame-integrated LED console Optional wireless ANT+ display
BATTERI	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
LADER	Giant EnergyPak smart charger 4A
FORBINDELSE	Giant RideControl App enabled, ANT+ wireless display signal with e-bike profile
RAMME	
STØRRELSER	S, M, ML, L, XL
FARVER	Meteor Storm
RAMME	Advanced-grade composite, 12x145 thru-axle
FORGAFFEL	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
KOMPONENTER	
STYR	Giant Contact SL D-Fuse 31.8 alloy
FREMPIND	Contact SL Aerolight 31.8 alloy
SADELPIND	Giant D-Fuse, Composite, 14mm offset
SADEL	Giant Approach
GEARGRUPPE	
SKIFTEGREB	Sram Rival AXS
FORSKIFTER	Sram Rival AXS
BAGSKIFTER	Sram Rival AXS
BREMSER	Sram Rival AXS HRD, Paceline 160mm 6-bols [F/R]
BREMSEGREB	Sram Rival AXS HRD
KASSETTE	Sram Rival XG-1250 10x36T 12-speed
KÆDE	Sram Rival 12-speed
KRANKSÆT	Sram Force X-SYNC 33/46T BCD107 chain ring Praxis E crank Alloy ISIS
KRANKBOKS	Giant E+ System BBSS

HJUL	
FÆLGE	Giant P-R2 Alloy Disc Wheel System, Tubeless Ready, 22mm inner width, 12mm thru-axle, w/ Sapim spoke E-Light [R] Race [F], e-bike optimized
DÆK	Giant Gavia Fondo 0, tubeless, 700x32, folding
EKSTRA	Fender adapter
TILBEHØR	
LYGTER	Seatpost clamp integrated tail light

Pris: 51.299,00 kr.

## GEOMETRI

RAMME	S	M	ML	L	XL
Sadelrørslængde (mm)	445	480	515	535	565
Sadelrørsinkel	74,0°	73,5°	73,0°	73,0°	73,0°
Overrørs slængde (mm)	530	545	560	575	590
Kronrørs slængde (mm)	130	145	167	187	205
Kronrørsinkel	71,5°	72,5°	72,5°	72,5°	72,5°
Forgaffel fremspring (rake) (mm)	50	50	50	50	50
Sti (mm)	56,1	58,6	58,6	58,6	58,6
Akselafstand (mm)	994	995	1008	1023	1037,9
Kædestagslængde (mm)	420	420	420	420	420
Krankboks drop (mm)	80	80	75	75	75
Stack (mm)	542	560	576	595	612,4
Reach (mm)	374	379	384	393	402,6
Skridthøjde (mm)	716	746	779	799	824
Styrbredde (mm)	400	420	420	440	440
Frempindslængde (mm)	90	100	110	110	120
Hjulstørrelse	700C	700C	700C	700C	700C

Alle de anførte specifikationer kan ændres uden varsel.