

DEFY ADVANCED E+ ELITE 2



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDriveMove Plus Hub drive 75Nm max
CONTROLLER	Mode support switch from SRAM Blips
DISPLAY	Giant RideControl GO, frame-integrated LED console Optional wireless ANT+ display
BATTERY	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
CHARGER	Giant EnergyPak 4A smart charger, 60% in 1:45
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
ΣΚΕΛΕΤΟΣ	
ΜΕΓΕΘΗ	S, M, ML, L, XL
ΧΡΩΜΑΤΑ	Sea Sparkle / Black
ΣΚΕΛΕΤΟΣ	Advanced-grade composite,12x145 thru-axle
ΠΙΠΟΥΝΙ	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
ΑΝΑΡΤΗΣΗ	-
ΕΞΑΡΤΗΜΑΤΑ	
ΤΙΜΟΝΙ	Giant Contact SL D-Fuse 31.8 alloy
ΛΑΙΜΟΣ ΤΙΜΟΝΙΟΥ	Contact SL Aerolight 31.8 alloy
ΛΑΙΜΟΣ ΣΈΛΛΑΣ	Giant D-Fuse, Composite, 14mm offset
ΣΈΛΛΑ	Giant Approach
ΜΕΤΑΔΟΣΗ	
ΛΕΒΙΕ ΤΑΧΥΤΗΤΩΝ	Sram Rival eTap AXS
ΝΤΕΡΑΓΙΕΡ ΕΜΠΡΟΣΘΙΟ	Sram Rival eTap AXS
ΝΤΕΡΑΓΙΕΡ ΟΠΙΣΘΙΟ.	Sram Rival eTap AXS
ΦΡΕΝΑ	Sram Rival eTap HRD, Paceline 160mm center-lock [F] 160mm 6-bols [R]
ΜΑΝΈΤΤΕΣ ΦΡΕΝΩΝ	Sram Rival eTap AXS HRD
CASETTE Η ΕΛΕΥΘΕΡΟ	Sram Rival XG-1250 10x36T 12-speed
ΑΛΥΣΙΔΑ	Sram Rival 12-speed
ΔΙΣΚΟΒΡΑΧΙΩΝΑΣ	"Sram Force X-SYNC 33/46T BCD107 chain ring Praxis E crank Alloy ISIS"
BOTTOM BRACKET	Giant E+ System BBSS

WHEELS	
ΣΤΕΦΑΝΙΑ	Giant P-R2 Alloy Disc Wheel System, Tubeless Ready, 22mm inner width, 12mm thru-axle
AKTINEΣ	Sapim spoke E-Light [R] Race [F], e-bike optimized
ΕΛΑΣΤΙΚΑ	Giant Gavia Fondo 0 700x32C 170TPI Tubeless Foldable
EXTRAS	Fender adapter
ACCESSORIES	
LIGHTING	Seatpost clamp integrated tail light

ΓΕΩΜΕΤΡΙΑ

ΣΚΕΛΕΤΟΣ	S	M	ML	L	XL
Seat Tube Length (mm)	445	480	515	535	565
Seat Tube Angle	74,0°	73,5°	73,0°	73,0°	73,0°
Top Tube Length (mm)	530	545	560	575	590
Head Tube Length (mm)	130	145	167	187	205
Head Tube Angle	71,5°	72,5°	72,5°	72,5°	72,5°
Fork Rake (mm)	50	50	50	50	50
Trail (mm)	65,1	58,6	58,6	58,6	58,6
Wheelbase (mm)	994,3	995,2	1007,5	1022,7	1037,9
Chain Stay Length (mm)	420	420	420	420	420
Bottom Bracket Drop (mm)	80	80	75	75	75
Stack (mm)	542,2	560,2	576,1	595,2	612,4
Reach (mm)	374,3	378,9	383,6	392,8	402,6
Stand Over Height (mm)	716	745,5	779	799	824
Handlebar Width (mm)	400	420	420	440	440
Stem Length (mm)	90	100	110	110	120
Crank Length (mm)	170	172,5	172,5	175	175
Wheel Size	700C	700C	700C	700C	700C

Όλες οι προδιαγραφές είναι δυνατό να αλλάξουν χωρίς πρότερη ειδοποίηση