

DEFY ADVANCED E+ ELITE 2

GIANT



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Move Plus, Rear Hub, 30Nm
CONTROLLER	Mode support switch from SRAM Blips
DISPLAY	Giant RideControl GO, frame-integrated LED console Optional wireless ANT+ display
BATTERY	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
CHARGER	Giant EnergyPak smart charger 4A
MAXIMUM ASSISTED SPEED	Pedal-assist limited to 25 km/h in accordance with Australian regulations (EN15194); no motor support above this speed
CONNECTIVITY	Giant RideControl App enabled, ANT+ wireless display signal with e-bike profile
FRAME	
SIZES	S, M, ML, L, XL
COLOURS	Mercury
FRAME	Advanced-grade composite, 12x145 thru-axle
FORK	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
COMPONENTS	
HANDLEBAR	Giant Contact SL D-Fuse S:38/41cm, M:40/43cm, ML:40/43cm, L:42/45cm, XL:42/45cm
STEM	Giant Contact SL AeroLight S:90mm, M:100mm, ML:110mm, L:110mm, XL:120mm
SEATPOST	Giant D-Fuse, Composite, 14mm offset
SADDLE	Giant Approach
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	SRAM Rival AXS HRD, ED-Rival-E1
FRONT DERAILLEUR	SRAM Rival AXS, FD-Rival-E-E1
REAR DERAILLEUR	SRAM Rival AXS, RD-Rival-E-E1
BRAKES	SRAM Rival AXS HRD, ED-Rival-E1, SRAM PaceLine rotors [F]160mm, [R]160mm
BRAKE LEVERS	SRAM Rival AXS HRD, ED-Rival-E1
CASSETTE	SRAM Rival E1 XG-1250, 12-speed, 10-33
CHAIN	SRAM Rival-E1, 12-speed
CRANKSET	SRAM Force X-SYNC 33/46T BCD107 chain ring Praxis E Crank Alloy ISIS, S:170mm, M:172.5mm, ML:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	Giant E+ System BBSS

WHEELS	
RIMS	Giant P-R2 Alloy Disc Wheel System, Tubeless Ready
HUBS	[F] Giant Alloy, 24H [R] Giant SyncDrive Move Plus, 28H
SPOKES	Sapim spoke E-Light [R] Race [F], e-bike optimised
TYRES	Giant Gavia Fondo 0, tubeless, 700x32, folding
EXTRAS	N/A
ACCESSORIES	
LIGHTING	Seatpost clamp integrated tail light
LIMITS	
MAX TYRE CLEARANCE	38mm

Price: \$10,999.00

GEOMETRY

FRAME	S	M	ML	L	XL
Seat Tube Length (mm)	445	480	515	535	565
Seat Tube Angle	74.0°	73.5°	73.0°	73.0°	73.0°
Top Tube Length (mm)	530	545	560	575	590
Head Tube Length (mm)	130	145	167	187	205
Head Tube Angle	71.5°	72.5°	72.5°	72.5°	72.5°
Fork Rake (mm)	50	50	50	50	50
Trail (mm)	56.1	58.6	58.6	58.6	58.6
Wheelbase (mm)	994	995	1008	1023	1037.9
Chain Stay Length (mm)	420	420	420	420	420
Bottom Bracket Drop (mm)	80	80	75	75	75
Stack (mm)	542	560	576	595	612.4
Reach (mm)	374	379	384	393	402.6
Stand Over Height (mm)	716	746	779	799	824
Stem Length (mm)	90	100	110	110	120
Wheel Size	700C	700C	700C	700C	700C

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.