

DEFY ADVANCED E+ ELITE 2



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDriveMove Plus Hub drive 75Nm max
CONTROLLER	Mode support switch from SRAM Blips
DISPLAY	Giant RideControl GO, frame-integrated LED console Optional wireless ANT+ display
BATTERY	EnergyPak Smart 400Wh by Panasonic, Aluminium casing with highest safety standard (UL2271, EN50604), CO2 Neutral production, 2300 charging cycles. EnergyPak Plus 200 range extender compatible
CHARGER	Giant EnergyPak 4A smart charger, 60% in 1:45
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
FRAME	
SIZES	S, M, ML, L, XL
COLOURS	Gloss Sea Sparkle / Black
FRAME	Advanced-grade composite, 12x145 thru-axle
FORK	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
SHOCK	-
COMPONENTS	
HANDLEBAR	Giant Contact SL D-Fuse 31.8 alloy
STEM	Contact SL Aerolight 31.8 alloy
SEATPOST	Giant D-Fuse, Composite, 14mm offset
SADDLE	Giant Approach
PEDALS	PEDALS NOT SUPPLIED
DRIVETRAIN	
SHIFTERS	Sram Rival eTap AXS 2x12
FRONT DERAILLEUR	Sram Rival eTap AXS
REAR DERAILLEUR	Sram Rival eTap AXS
BRAKES	Sram Rival eTap HRD, Paceline 160mm center-lock [F] 160mm 6-bols [R]
BRAKE LEVERS	Sram Rival eTap AXS HRD
CASSETTE	Sram Rival XG-1250 10x36T 12-speed
CHAIN	Sram Rival 12-speed
CRANKSET	Sram Rival X-SYNC 33/46T BCD107 chain ring Praxis E Crank Carbon ISIS
BOTTOM BRACKET	Giant E+ System BBSS

WHEELS	
RIMS	Giant P-R2 Alloy Disc Wheel System, Tubeless Ready, 22mm inner width, 12mm thru-axle, w/ Sapim spoke E-Light [R] Race [F], e-bike optimised
SPOKES	Sapim spoke E-Light [R] Race [F], e-bike optimised
TYRES	Giant Gavia Fondo 0 700x32C 170TPI Tubeless Foldable
EXTRAS	Fender adapter
ACCESSORIES	
LIGHTING	Seatpost clamp integrated tail light

Price: €7,299.00

GEOMETRY

FRAME	M	ML	L	XL
Seat Tube Length (mm)	480	515	535	565
Seat Tube Angle	73.5°	73.0°	73.0°	73.0°
Top Tube Length (mm)	545	560	575	590
Head Tube Length (mm)	145	167	187	205
Head Tube Angle	72.5°	72.5°	72.5°	72.5°
Fork Rake (mm)	50	50	50	50
Trail (mm)	58.6	58.6	58.6	58.6
Wheelbase (mm)	995.2	1007.5	1022.7	1037.9
Chain Stay Length (mm)	420	420	420	420
Bottom Bracket Drop (mm)	80	75	75	75
Stack (mm)	560.2	576.1	595.2	612.4
Reach (mm)	378.9	383.6	392.8	402.6
Stand Over Height (mm)	745.5	779	799	824
Handlebar Width (mm)	420	420	440	440
Stem Length (mm)	100	110	110	120
Crank Length (mm)	172.5	172.5	175	175
Wheel Size	700C	700C	700C	700C

All specifications listed are subject to change without notice.