

DEFY ADVANCED E+ ELITE 2

GIANT



SPECS

HYBRID CYCLING TECHNOLOGY

| | |
|---------------------|--|
| MOTOR | SyncDriveMove Plus Hub drive 75Nm max |
| CONTROLLER | Mode support switch from SRAM Blips |
| DISPLAY | Giant RideControl GO, frame-integrated LED console Optional wireless ANT+ display |
| BATTERY | Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible |
| CHARGER | Giant EnergyPak smart charger 4A |
| CONNECTIVITY | Giant RideControl App enabled, ANT+ wireless display signal with e-bike profile |

FRAME

| | |
|----------------|--|
| SIZES | S, M, ML, L, XL |
| COLOURS | Meteor Storm |
| FRAME | Advanced-grade composite, 12x145 thru-axle |
| FORK | Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc |

COMPONENTS

| | |
|-------------------------|--|
| HANDLEBAR | Giant Contact SL D-Fuse 31.8 alloy |
| STEM | Contact SL Aerolight 31.8 alloy |
| SEATPOST | Giant D-Fuse, Composite, 14mm offset |
| SADDLE | Giant Approach |
| DRIVETRAIN | |
| SHIFTERS | Sram Rival AXS |
| FRONT DERAILLEUR | Sram Rival AXS |
| REAR DERAILLEUR | Sram Rival AXS |
| BRAKES | Sram Rival AXS HRD, Paceline 160mm 6-bols [F/R] |
| BRAKE LEVERS | Sram Rival AXS HRD |
| CASSETTE | Sram Rival XG-1250 10x36T 12-speed |
| CHAIN | Sram Rival 12-speed |
| CRANKSET | Sram Force X-SYNC 33/46T BCD107 chain ring Praxis E crank Alloy ISIS |
| BOTTOM BRACKET | Giant E+ System BBSS |

WHEELS

| | |
|---------------|---|
| RIMS | Giant P-R2 Alloy Disc Wheel System, Tubeless Ready, 22mm inner width, 12mm thru-axle, w/ Sapim spoke E-Light [R] Race [F], e-bike optimized |
| TYRES | Giant Gavia Fondo 0, tubeless, 700x32, folding |
| EXTRAS | Fender adapter |

ACCESSORIES

| | |
|-----------------|--------------------------------------|
| LIGHTING | Seatpost clamp integrated tail light |
|-----------------|--------------------------------------|

Price: €7,199.00

GEOMETRY

| FRAME | S | M | ML | L | XL |
|--------------------------|-------|-------|-------|-------|--------|
| Seat Tube Length (mm) | 445 | 480 | 515 | 535 | 565 |
| Seat Tube Angle | 74.0° | 73.5° | 73.0° | 73.0° | 73.0° |
| Top Tube Length (mm) | 530 | 545 | 560 | 575 | 590 |
| Head Tube Length (mm) | 130 | 145 | 167 | 187 | 205 |
| Head Tube Angle | 71.5° | 72.5° | 72.5° | 72.5° | 72.5° |
| Fork Rake (mm) | 50 | 50 | 50 | 50 | 50 |
| Trail (mm) | 56.1 | 58.6 | 58.6 | 58.6 | 58.6 |
| Wheelbase (mm) | 994 | 995 | 1008 | 1023 | 1037.9 |
| Chain Stay Length (mm) | 420 | 420 | 420 | 420 | 420 |
| Bottom Bracket Drop (mm) | 80 | 80 | 75 | 75 | 75 |
| Stack (mm) | 542 | 560 | 576 | 595 | 612.4 |
| Reach (mm) | 374 | 379 | 384 | 393 | 402.6 |
| Stand Over Height (mm) | 716 | 746 | 779 | 799 | 824 |
| Handlebar Width (mm) | 400 | 420 | 420 | 440 | 440 |
| Stem Length (mm) | 90 | 100 | 110 | 110 | 120 |
| Wheel Size | 700C | 700C | 700C | 700C | 700C |

All specifications listed are subject to change without notice.