

DEFY ADVANCED E+ ELITE 2

GIANT



SPECIFICATIES

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDriveMove Plus Hub drive 75Nm max
BEDIENINGSUNIT	Mode support switch from SRAM Blips
DISPLAY	Giant RideControl GO, frame-integrated LED console Optional wireless ANT+ display
ACCU	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
LADER	Giant EnergyPak smart charger 4A
CONNECTIVITY	Giant RideControl App enabled, ANT+ wireless display signal with e-bike profile
FRAME	
MATEN	S, M, ML, L, XL
KLEUREN	Meteor Storm
FRAME	Advanced-grade composite, 12x145 thru-axle
VOORVORK	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
ONDERDELEN	
STUUR	Giant Contact SL D-Fuse 31.8 alloy
STUURPEN	Contact SL Aerolight 31.8 alloy
ZADELPEN	Giant D-Fuse, Composite, 14mm offset
ZADEL	Giant Approach
AFMONTAGE	
SHIFTERS	Sram Rival AXS
VOORDERAILLEUR	Sram Rival AXS
ACHTERDERAILLEUR	Sram Rival AXS
REMMEN	Sram Rival AXS HRD, Paceline 160mm 6-bols [F/R]
REMHENDELS	Sram Rival AXS HRD
CASSETTE	Sram Rival XG-1250 10x36T 12-speed
AANDRIJVING	Sram Rival 12-speed
CRANKSET	Sram Force X-SYNC 33/46T BCD107 chain ring Praxis E crank Alloy ISIS
BOTTOM BRACKET	Giant E+ System BBSS

WIELSET	
VELGEN	Giant P-R2 Alloy Disc Wheel System, Tubeless Ready, 22mm inner width, 12mm thru-axle, w/ Sapim spoke E-Light [R] Race [F], e-bike optimized
BANDEN	Giant Gavia Fondo 0, tubeless, 700x32, folding
EXTRA'S	Fender adapter
ACCESSOIRES	
VERLICHTING	Seatpost clamp integrated tail light

Adviesprijs: € 6.499,00

GEOMETRIE

FRAME	S	M	ML	L	XL
Zitbuis Lengte (mm)	445	480	515	535	565
Zitbuis Hoek	74,0°	73,5°	73,0°	73,0°	73,0°
Frame Lengte (horizontaal) (mm)	530	545	560	575	590
Balhoofdbuis Lengte (mm)	130	145	167	187	205
Balhoofdbuis Hoek	71,5°	72,5°	72,5°	72,5°	72,5°
Vork Sprong (mm)	50	50	50	50	50
Wielbasis (mm)	994	995	1008	1023	1037,9
Liggende achtervork lengte (mm)	420	420	420	420	420
Bottom Bracket Drop (mm)	80	80	75	75	75
Stack (mm)	542	560	576	595	612,4
Reach (mm)	374	379	384	393	402,6
Stand Over Height (mm)	716	746	779	799	824
Stuur breedte (mm)	400	420	420	440	440
Stuurpen Lengte (mm)	90	100	110	110	120
Wielmaat	700C	700C	700C	700C	700C

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.