

DEFY ADVANCED E+ ELITE 2

GIANT



SPECIFICATIES

HYBRID CYCLING TECHNOLOGY

MOTOR	SyncDriveMove Plus Hub drive 30Nm (comparable to 75Nm mid-drive motor)
BEDIENINGSUNIT	Mode support switch from SRAM Blips
DISPLAY	Giant RideControl GO, frame-integrated LED console Optional wireless ANT+ display
ACCU	Giant EnergyPak SMART 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
LADER	Giant EnergyPak 4A smart charger, 60% in 1:45
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile

FRAME

MATEN	S, M, ML, L, XL
KLEUREN	Sea Sparkle / Black
FRAME	Advanced-grade composite, 12x145 thru-axle
VOORVORK	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
DEMPER	-

ONDERDELEN

STUUR	Giant Contact SL D-Fuse 31.8 alloy
STUURPEN	Contact SL Aerolight 31.8 alloy
ZADELPEN	Giant D-Fuse, Composite, 14mm offset
ZADEL	Giant Approach

AFMONTAGE

SHIFTERS	Sram Rival eTap AXS
VOORDERAILLEUR	Sram Rival eTap AXS
ACHTERDERAILLEUR	Sram Rival eTap AXS
REMMEN	Sram Rival eTap HRD, Paceline 160mm center-lock [F] 160mm 6-bols [R]
REMHENDELS	Sram Rival eTap AXS HRD
CASSETTE	Sram Rival XG-1250 10x36T 12-speed
AANDRIJVING	Sram Rival 12-speed
CRANKSET	"Sram Force X-SYNC 33/46T BCD107 chain ring Praxis E crank Alloy ISIS"
BOTTOM BRACKET	Giant E+ System BBSS

WIELSET

VELGEN	Giant P-R2 Alloy Disc Wheel System, Tubeless Ready, 22mm inner width, 12mm thru-axle
SPAKEN	Sapim spoke E-Light [R] Race [F], e-bike optimized
BANDEN	Giant Gavia Fondo 0 700x32C 170TPI Tubeless Foldable
EXTRA'S	Fender adapter

ACCESSOIRES

VERLICHTING	Seatpost clamp integrated tail light
--------------------	--------------------------------------

Adviesprijs: € 6.499,00

GEOMETRIE

FRAME	S	M	ML	L	XL
Zitbuis lengte (mm)	445	480	515	535	565
Zitbuis hoek	74,0°	73,5°	73,0°	73,0°	73,0°
Frame Lengte (horizontaal) (mm)	530	545	560	575	590
Balhoofdbuis Lengte (mm)	130	145	167	187	205
Balhoofdbuis Hoek	71,5°	72,5°	72,5°	72,5°	72,5°
Vork Sprong (mm)	50	50	50	50	50
Naloop (mm)	65,1	58,6	58,6	58,6	58,6
Wielbasis (mm)	994,3	995,2	1007,5	1022,7	1037,9
Liggende achtervork lengte (mm)	420	420	420	420	420
Bottom Bracket Drop (mm)	80	80	75	75	75
Stack (mm)	542,2	560,2	576,1	595,2	612,4
Reach (mm)	374,3	378,9	383,6	392,8	402,6
Stand Over Height (mm)	716	745,5	779	799	824
Stuur breedte (mm)	400	420	420	440	440
Stuurpen Lengte (mm)	90	100	110	110	120
Cranklengte (mm)	170	172,5	172,5	175	175
Wielmaat	700C	700C	700C	700C	700C

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.