

# DEFY ADVANCED E+ ELITE 2

**GIANT**



## SPECIFICATIES

HYBRID CYCLING TECHNOLOGY	
<b>MOTOR</b>	SyncDriveMove Plus Hub drive 75Nm max
<b>BEDIENINGSUNIT</b>	Mode support switch from SRAM Blips
<b>DISPLAY</b>	Giant RideControl GO, frame-integrated LED console Optional wireless ANT+ display
<b>ACCU</b>	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
<b>LADER</b>	Giant EnergyPak smart charger 4A
<b>CONNECTIVITY</b>	Giant RideControl App enabled, ANT+ wireless display signal with e-bike profile
FRAME	
<b>MATEN</b>	S, M, ML, L, XL
<b>KLEUREN</b>	Meteor Storm
<b>FRAME</b>	Advanced-grade composite, 12x145 thru-axle
<b>VOORVORK</b>	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
ONDERDELEN	
<b>STUUR</b>	Giant Contact SL D-Fuse 31.8 alloy
<b>STUURPEN</b>	Contact SL Aerolight 31.8 alloy
<b>ZADELLEN</b>	Giant D-Fuse, Composite, 14mm offset
<b>ZADEL</b>	Giant Approach
AFMONTAGE	
<b>SHIFTERS</b>	Sram Rival AXS
<b>VOORDERAILLEUR</b>	Sram Rival AXS
<b>ACHTERDERAILLEUR</b>	Sram Rival AXS
<b>REMMEN</b>	Sram Rival AXS HRD, Paceline 160mm 6-bols [F/R]
<b>REMHENDELS</b>	Sram Rival AXS HRD
<b>CASSETTE</b>	Sram Rival XG-1250 10x36T 12-speed
<b>AANDRIJVING</b>	Sram Rival 12-speed
<b>CRANKSET</b>	Sram Force X-SYNC 33/46T BCD107 chain ring Praxis E crank Alloy ISIS
<b>BOTTOM BRACKET</b>	Giant E+ System BBSS

WIELSET	
<b>VELGEN</b>	Giant P-R2 Alloy Disc Wheel System, Tubeless Ready, 22mm inner width, 12mm thru-axle, w/ Sapim spoke E-Light [R] Race [F], e-bike optimized
<b>BANDEN</b>	Giant Gavia Fondo 0, tubeless, 700x32, folding
<b>EXTRA'S</b>	Fender adapter
ACCESSOIRES	
<b>VERLICHTING</b>	Seatpost clamp integrated tail light

**Adviesprijs: € 6.499,00**

## GEOMETRIE

FRAME	S	M	ML	L	XL
Zitbuis lengte (mm)	445	480	515	535	565
Zitbuis hoek	74,0°	73,5°	73,0°	73,0°	73,0°
Frame Lengte (horizontaal) (mm)	530	545	560	575	590
Balhoofdbuis Lengte (mm)	130	145	167	187	205
Balhoofdbuis Hoek	71,5°	72,5°	72,5°	72,5°	72,5°
Vork Sprong (mm)	50	50	50	50	50
Naloop (mm)	56,1	58,6	58,6	58,6	58,6
Wielbasis (mm)	994	995	1008	1023	1037,9
Liggende achtervork lengte (mm)	420	420	420	420	420
Bottom Bracket Drop (mm)	80	80	75	75	75
Stack (mm)	542	560	576	595	612,4
Reach (mm)	374	379	384	393	402,6
Stand Over Height (mm)	716	746	779	799	824
Stuur breedte (mm)	400	420	420	440	440
Stuurpen Lengte (mm)	90	100	110	110	120
Wielmaat	700C	700C	700C	700C	700C

*Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder vooraankondiging wijzigen.*