

DEFY ADVANCED E+ ELITE 2

GIANT



SPECS

TECNOLOGIA HÍBRIDA DE CICLISMO	
MOTOR	SyncDriveMove Plus Hub drive 75Nm max
SENSOR	Mode support switch from SRAM Blips
ECRÃ	Giant RideControl GO, frame-integrated LED console Optional wireless ANT+ display
BATERIA	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
CARREGADOR	Giant EnergyPak smart charger 4A
CONNECTIVITY	Giant RideControl App enabled, ANT+ wireless display signal with e-bike profile
QUADRO	
TAMANHOS	S, M, ML, L, XL
CORES	Meteor Storm
QUADRO	Advanced-grade composite, 12x145 thru-axle
FORQUILHA	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
COMPONENTES	
GUIADOR	Giant Contact SL D-Fuse 31.8 alloy
AVANÇO	Contact SL Aerolight 31.8 alloy
ESPIGÃO DE SELIM	Giant D-Fuse, Composite, 14mm offset
SELIM	Giant Approach
TRANSMISSÃO	
MANETES	Sram Rival AXS
DESVIADOR DIANTEIRO	Sram Rival AXS
DESVIADOR TRASEIRO	Sram Rival AXS
TRAVÕES	Sram Rival AXS HRD, Paceline 160mm 6-bols [F/R]
MANÍPULOS DOS TRAVÕES	Sram Rival AXS HRD
CASSETTE	Sram Rival XG-1250 10x36T 12-speed
CORRENTE	Sram Rival 12-speed
CONJUNTO PEDALEIRO	Sram Force X-SYNC 33/46T BCD107 chain ring Praxis E crank Alloy ISIS
MOVIMENTO CENTRAL	Giant E+ System BBSS

RODAS	
AROS	Giant P-R2 Alloy Disc Wheel System, Tubeless Ready, 22mm inner width, 12mm thru-axle, w/ Sapim spoke E-Light [R] Race [F], e-bike optimized
PNEUS	Giant Gavia Fondo 0, tubeless, 700x32, folding
EXTRAS	Fender adapter
ACESSÓRIOS	
LUZES	Seatpost clamp integrated tail light

Preço: 5 699,00 €

GEOMETRIA

QUADRO	S	M	ML	L	XL
Comprimento do tubo do assento (mm)	445	480	515	535	565
Ângulo do tubo do assento	74,0°	73,5°	73,0°	73,0°	73,0°
Comprimento do tubo superior (mm)	530	545	560	575	590
Comprimento do tubo principal (mm)	130	145	167	187	205
Ângulo do tubo principal	71,5°	72,5°	72,5°	72,5°	72,5°
Garfo ancinho (mm)	50	50	50	50	50
Trilha (mm)	56,1	58,6	58,6	58,6	58,6
distância entre eixos (mm)	994	995	1008	1023	1037,9
Comprimento Chain Stay (mm)	420	420	420	420	420
Suporte inferior (mm)	80	80	75	75	75
Pilha (mm)	542	560	576	595	612,4
Alcançar (mm)	374	379	384	393	402,6
Altura do standover (mm)	716	746	779	799	824
Largura do guidão (mm)	400	420	420	440	440
Comprimento da haste (mm)	90	100	110	110	120
Tamanho da roda	700C	700C	700C	700C	700C

Todas as especificações apresentadas estão sujeitas a alterações sem aviso prévio.