

DEFY ADVANCED E+ ELITE 2



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDriveMove Plus Hub drive 75Nm max
SENSOR	Mode support switch from SRAM Blips
DISPLAY	Giant RideControl GO, frame-integrated LED console Optional wireless ANT+ display
BATTERY	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
CHARGER	Giant EnergyPak 4A smart charger, 60% in 1:45
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
CADRU	
MARIMI	S, M, ML, L, XL
CULORI	Sea Sparkle / Black
CADRU	Advanced-grade composite,12x145 thru-axle
FURCA	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
SOC	-
COMPONENTE	
GHIDON	Giant Contact SL D-Fuse 31.8 alloy
PIPA	Contact SL Aerolight 31.8 alloy
TIJA SA	Giant D-Fuse, Composite, 14mm offset
SA	Giant Approach
SISTEMUL DE SCHIMBARE A VITEZELOR	
MANETE SCHIMBATOR	Sram Rival eTap AXS
SCHIMBATOR FATA	Sram Rival eTap AXS
SCHIMBATOR SPATE	Sram Rival eTap AXS
FRANE	Sram Rival eTap HRD, Paceline 160mm center-lock [F] 160mm 6-bols [R]
MANETE FRANA	Sram Rival eTap AXS HRD
PINIOANE	Sram Rival XG-1250 10x36T 12-speed
LANT	Sram Rival 12-speed
ANGRENAJ	"Sram Force X-SYNC 33/46T BCD107 chain ring Praxis E crank Alloy ISIS"
BOTTOM BRACKET	Giant E+ System BBSS

ROTI	
JANTE	Giant P-R2 Alloy Disc Wheel System, Tubeless Ready, 22mm inner width, 12mm thru-axle
SPITE	Sapim spoke E-Light [R] Race [F], e-bike optimized
ANVELOPE	Giant Gavia Fondo 0 700x32C 170TPI Tubeless Foldable
EXTRAS	Fender adapter
ACCESSORIES	
LIGHTING	Seatpost clamp integrated tail light

GEOMETRIE

CADRU	S	M	ML	L	XL
Seat Tube Length (mm)	445	480	515	535	565
Seat Tube Angle	74,0°	73,5°	73,0°	73,0°	73,0°
Top Tube Length (mm)	530	545	560	575	590
Head Tube Length (mm)	130	145	167	187	205
Head Tube Angle	71,5°	72,5°	72,5°	72,5°	72,5°
Fork Rake (mm)	50	50	50	50	50
Trail (mm)	65,1	58,6	58,6	58,6	58,6
Wheelbase (mm)	994,3	995,2	1007,5	1022,7	1037,9
Chain Stay Length (mm)	420	420	420	420	420
Bottom Bracket Drop (mm)	80	80	75	75	75
Stack (mm)	542,2	560,2	576,1	595,2	612,4
Reach (mm)	374,3	378,9	383,6	392,8	402,6
Stand Over Height (mm)	716	745,5	779	799	824
Handlebar Width (mm)	400	420	420	440	440
Stem Length (mm)	90	100	110	110	120
Crank Length (mm)	170	172,5	172,5	175	175
Wheel Size	700C	700C	700C	700C	700C

Toate specificatiile enumerate se pot schimba fara notificare prealabila.