

DEFY ADVANCED E+ ELITE 2

GIANT



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDriveMove Plus Hub drive 75Nm max
SENSOR	Mode support switch from SRAM Blips
DISPLAY	Giant RideControl GO, frame-integrated LED console Optional wireless ANT+ display
BATTERY	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
CHARGER	Giant EnergyPak smart charger 4A
CONNECTIVITY	Giant RideControl App enabled, ANT+ wireless display signal with e-bike profile
CADRU	
MARIMI	S, M, ML, L, XL
CULORI	Meteor Storm
CADRU	Advanced-grade composite,12x145 thru-axle
FURCA	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
COMPONENTE	
GHIDON	Giant Contact SL D-Fuse 31.8 alloy
PIPA	Contact SL Aerolight 31.8 alloy
TIJA SA	Giant D-Fuse, Composite, 14mm offset
SA	Giant Approach
SISTEMUL DE SCHIMBARE A VITEZELOR	
MANETE SCHIMBATOR	Sram Rival AXS
SCHIMBATOR FATA	Sram Rival AXS
SCHIMBATOR SPATE	Sram Rival AXS
FRANE	Sram Rival AXS HRD, Paceline 160mm 6-bols [F/R]
MANETE FRANA	Sram Rival AXS HRD
PINIOANE	Sram Rival XG-1250 10x36T 12-speed
LANT	Sram Rival 12-speed
ANGRENAJ	Sram Force X-SYNC 33/46T BCD107 chain ring Praxis E crank Alloy ISIS
BOTTOM BRACKET	Giant E+ System BBSS

ROTI	
JANTE	Giant P-R2 Alloy Disc Wheel System, Tubeless Ready, 22mm inner width, 12mm thru-axle, w/ Sapim spoke E-Light [R] Race [F], e-bike optimized
ANVELOPE	Giant Gavia Fondo 0, tubeless, 700x32, folding
EXTRAS	Fender adapter
ACCESSORIES	
LIGHTING	Seatpost clamp integrated tail light

GEOMETRIE

CADRU	S	M	ML	L	XL
Seat Tube Length (mm)	445	480	515	535	565
Seat Tube Angle	74,0°	73,5°	73,0°	73,0°	73,0°
Top Tube Length (mm)	530	545	560	575	590
Head Tube Length (mm)	130	145	167	187	205
Head Tube Angle	71,5°	72,5°	72,5°	72,5°	72,5°
Fork Rake (mm)	50	50	50	50	50
Trail (mm)	56,1	58,6	58,6	58,6	58,6
Wheelbase (mm)	994	995	1008	1023	1037,9
Chain Stay Length (mm)	420	420	420	420	420
Bottom Bracket Drop (mm)	80	80	75	75	75
Stack (mm)	542	560	576	595	612,4
Reach (mm)	374	379	384	393	402,6
Stand Over Height (mm)	716	746	779	799	824
Handlebar Width (mm)	400	420	420	440	440
Stem Length (mm)	90	100	110	110	120
Wheel Size	700C	700C	700C	700C	700C

Toate specificatiile enumerate se pot schimba fara notificare prealabila.