



SPECIFIKACIJE

HIBRIDNA GONILNA TEHNOLOGIJA	
MOTOR	SyncDriveMove Plus Hub drive 75Nm max
TIPALO	Mode support switch from SRAM Blips
PRIKAZOVALNIK	Giant RideControl GO, frame-integrated LED console Optional wireless ANT+ display
BATERIJA	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
CHARGER	Giant EnergyPak 4A smart charger, 60% in 1:45
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
OKVIR	
VELIKOSTI	S, M, ML, L, XL
BARVE	Sea Sparkle / Black
OKVIR	Advanced-grade composite,12x145 thru-axle
VILICE	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
AMORTIZER	
-	
KOMPONENTE	
KRMILO	Giant Contact SL D-Fuse 31.8 alloy
OPORA KRMILA	Contact SL Aerolight 31.8 alloy
OPORA SEDEŽA	Giant D-Fuse, Composite, 14mm offset
SEDEŽ	Giant Approach
POGON	
PRESTAVNE ROČICE	Sram Rival eTap AXS
PREDNJI MENJALNIK	Sram Rival eTap AXS
ZADNJI MENJALNIK	Sram Rival eTap AXS
ZAVORE	Sram Rival eTap HRD, Paceline 160mm center-lock [F] 160mm 6-bols [R]
ZAVORNE ROČICE	Sram Rival eTap AXS HRD
VERIŽNIK	Sram Rival XG-1250 10x36T 12-speed
VERIGA	Sram Rival 12-speed
GONILKE Z VERIŽNIKI	"Sram Force X-SYNC 33/46T BCD107 chain ring Praxis E crank Alloy ISIS"
BOTTOM BRACKET	Giant E+ System BBSS

OBROČNIKI	
OBROČI	Giant P-R2 Alloy Disc Wheel System, Tubeless Ready, 22mm inner width, 12mm thru-axle
NAPERE	Sapim spoke E-Light [R] Race [F], e-bike optimized
PLAŠČI	Giant Gavia Fondo 0 700x32C 170TPI Tubeless Foldable
DODATKI	Fender adapter
DODATNA OPREMA	
SVETILA	Seatpost clamp integrated tail light

GEOMETRIJA

OKVIR	S	M	ML	L	XL
Dolžina sedežne cevi (mm)	445	480	515	535	565
Kot sedežne cevi	74,0°	73,5°	73,0°	73,0°	73,0°
Top Tube Length (mm)	530	545	560	575	590
Višina glave okvirja (mm)	130	145	167	187	205
Krmilni kot	71,5°	72,5°	72,5°	72,5°	72,5°
Zamik vpetja osi (mm)	50	50	50	50	50
Trail (mm)	65,1	58,6	58,6	58,6	58,6
Medosna razdalja (mm)	994,3	995,2	1007,5	1022,7	1037,9
Dolžina cevi ob verigi (mm)	420	420	420	420	420
Bottom Bracket Drop (mm)	80	80	75	75	75
Oddaljenost zgornje cevi od gonilne osi (mm)	542,2	560,2	576,1	595,2	612,4
Doseg (mm)	374,3	378,9	383,6	392,8	402,6
Višina zgornje cevi (mm)	716	745,5	779	799	824
Širina krmila (mm)	400	420	420	440	440
Dolžina opore krmila (mm)	90	100	110	110	120
Dolžina gonilke (mm)	170	172,5	172,5	175	175
Velikost obročnikov	700C	700C	700C	700C	700C

Vse navedene specifikacije se lahko spremenijo brez obvestila.