

DEFY ADVANCED E+ ELITE 2

GIANT



СПЕЦИФІКАЦІЯ

ТЕХНОЛОГІЯ HYBRID CYCLING

ДВИГУН	SyncDriveMove Plus Hub drive 75Nm max
КОНТРОЛЕР	Mode support switch from SRAM Blips
ДИСПЛЕЙ	Giant RideControl GO, frame-integrated LED console Optional wireless ANT+ display
БАТАРЕЯ	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
CHARGER	Giant EnergyPak smart charger 4A
CONNECTIVITY	Giant RideControl App enabled, ANT+ wireless display signal with e-bike profile

РАМА

РОЗМІР	S, M, ML, L, XL
КОЛІР	Meteor Storm
КОНСТРУКЦІЯ	Advanced-grade composite, 12x145 thru-axle
ВИЛКА	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc

КОМПОНЕНТИ

КЕРМО	Giant Contact SL D-Fuse 31.8 alloy
ВИНОС КЕРМА	Contact SL Aerolight 31.8 alloy
ВИНОС СІДЛА	Giant D-Fuse, Composite, 14mm offset
СІДЛО	Giant Approach
ПРИВІД	
МАНЕТКИ	Sram Rival AXS
ПЕРЕМИКАЧ ПЕРЕДНІЙ	Sram Rival AXS
ПЕРЕМИКАЧ ЗАДНІЙ	Sram Rival AXS
ГАЛЬМА	Sram Rival AXS HRD, Paceline 160mm 6-bols [F/R]
ВАЖЕЛІ ГАЛЬМ	Sram Rival AXS HRD
КАСЕТА	Sram Rival XG-1250 10x36T 12-speed
ЛАНЦЮГ	Sram Rival 12-speed
СИСТЕМА ШАТУНІВ	Sram Force X-SYNC 33/46T BCD107 chain ring Praxis E crank Alloy ISIS
КАРЕТКА	Giant E+ System BBSS

КОЛЕСА

ОБОДИ	Giant P-R2 Alloy Disc Wheel System, Tubeless Ready, 22mm inner width, 12mm thru-axle, w/ Sapim spoke E-Light [R] Race [F], e-bike optimized
ШИНИ	Giant Gavia Fondo 0, tubeless, 700x32, folding
ДОДАТКОВО	Fender adapter

АКСЕСУАРИ

ОСВІТЛЕННЯ	Seatpost clamp integrated tail light
------------	--------------------------------------

ГЕОМЕТРІЯ

РАМА	S	M	ML	L	XL
Довжина підсідельної труби (mm)	445	480	515	535	565
Нахил підсідельної труби	74,0°	73,5°	73,0°	73,0°	73,0°
Довжина верхньої труби (mm)	530	545	560	575	590
Висота кермової труби (mm)	130	145	167	187	205
Нахил кермової труби	71,5°	72,5°	72,5°	72,5°	72,5°
Виліт вилки (mm)	50	50	50	50	50
Шлях вилки (mm)	56,1	58,6	58,6	58,6	58,6
Колісна база (mm)	994	995	1008	1023	1037,9
Довжина нижнього пір'я рами (mm)	420	420	420	420	420
Провисання каретки (mm)	80	80	75	75	75
Ефективна висота (mm)	542	560	576	595	612,4
Ефективна довжина (mm)	374	379	384	393	402,6
Безпечна висота (mm)	716	746	779	799	824
Ширина керма (mm)	400	420	420	440	440
Довжина виносу (mm)	90	100	110	110	120
Розмір коліс	700C	700C	700C	700C	700C

Giant залишає за собою право змінювати специфікації без попереднього повідомлення.