

DEFY ADVANCED E+ ELITE AR

GIANT



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Move Plus, Rear Hub, 30Nm
CONTROLLER	Mode support switch from SRAM blips
DISPLAY	RideControl GO, frame integrated LED display ANT+ Wireless display compatible
BATTERY	EnergyPak Smart 400Wh EnergyPak Plus, range extender compatible
CHARGER	EnergyPak 4A smart charger compact
MAXIMUM ASSISTED SPEED	Pedal-assist limited to 25 km/h in accordance with Australian regulations (EN15194); no motor support above this speed
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
FRAME	
SIZES	S, M, M/L, L, XL
COLOURS	Kelp Forest
FRAME	Advanced-Grade Composite, disc, 12x145mm
FORK	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, disc, 12x100mm
SHOCK	-
COMPONENTS	
HANDLEBAR	Giant Contact SL D-Fuse S:40/42cm, M:42/44cm, M/L:42/44cm, L:44/46cm, XL:44/46cm
GRIPS	Stratus Lite 3.0
STEM	Giant Contact SL AeroLight S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
SEATPOST	Giant D-Fuse, composite, -5/+15mm offset
SADDLE	Giant Approach
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	SRAM Rival AXS
FRONT DERAILLEUR	-
REAR DERAILLEUR	SRAM Rival XPLR AXS
BRAKES	SRAM Rival AXS hydraulic, SRAM PaceLine rotors [F]160mm, [R]160mm
BRAKE LEVERS	SRAM Rival AXS hydraulic
CASSETTE	SRAM Rival XPLR XG-1251, 12-speed, 10-44
CHAIN	SRAM Rival D1
CRANKSET	SRAM X-SYNC 46T BCD107 chain ring Praxis E Crank Alloy ISIS, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	Giant E+ System BBSS

WHEELS	
RIMS	Giant P-X2 Alloy Disc Wheel System, Tubeless Ready
HUBS	[F] Giant Alloy, 24H [R] Giant SyncDrive Move Plus, 28H
SPOKES	Sapim spoke E-Light [R] Race [F], e-bike optimised
TYRES	Schwalbe G-one Allround Perf, RaceGuard, Brown side-wall 700x35C Tubeless
ACCESSORIES	
LIGHTING	Seatpost clamp integrated tail light
LIMITS	
MAX TYRE CLEARANCE	38mm

Price: \$10,499.00

GEOMETRY

FRAME	S	M	ML	L	XL
Seat Tube Length (mm)	445	480	515	535	565
Seat Tube Angle	74.0°	73.5°	73.0°	73.0°	73.0°
Top Tube Length (mm)	530	545	560	575	590
Head Tube Length (mm)	130	145	167	187	205
Head Tube Angle	71.5°	72.5°	72.5°	72.5°	72.5°
Fork Rake (mm)	50	50	50	50	50
Trail (mm)	65.1	58.6	58.6	58.6	58.6
Wheelbase (mm)	994.3	995.2	1007.5	1022.7	1037.9
Chain Stay Length (mm)	420	420	420	420	420
Bottom Bracket Drop (mm)	80	80	75	75	75
Stack (mm)	542.2	560.2	576.1	595.2	612.4
Reach (mm)	374.3	378.9	383.6	392.8	402.6
Stand Over Height (mm)	716	745.5	779	799	824
Stem Length (mm)	90	100	110	110	120
Crank Length (mm)	170	172.5	172.5	175	175
Wheel Size	700C	700C	700C	700C	700C

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.