DEFY ADVANCED E+ ELITE AR

SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Move Plus, Rear Hub, 30Nm
CONTROLLER	Mode support switch from SRAM Blips
DISPLAY	Giant RideControl GO, frame-integrated LED console Optional wireless ANT+ display
BATTERY	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
CHARGER	Giant EnergyPak smart charger 4A
MAXIMUM ASSISTED SPEED	Pedal-assist limited to 25 km/h in accordance with Australian regulations (EN15194); no motor support above this speed
CONNECTIVITY	Giant RideControl App enabled, ANT+ wireless display signal with e-bike profile
FRAME	
SIZES	S, M, ML, L, XL
COLOURS	Midnight Moon
FRAME	Advanced-grade composite,12x145 thru-axle
FORK	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
SHOCK	-
COMPONENTS	
HANDLEBAR	Giant Contact SL D-Fuse S:38/41cm, M:40/43cm, M/L:40/43cm, L:42/45cm, XL:42/45cm
STEM	Giant Contact SL AeroLight S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
SEATPOST	Giant D-Fuse, Composite, 14mm offset
SADDLE	Giant Approach
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	SRAM Rival AXS
FRONT DERAILLEUR	n/a
REAR DERAILLEUR	SRAM Rival XPLR AXS
BRAKES	SRAM Rival AXS hydraulic, SRAM PaceLine rotors [F]160mm, [R]160mm
BRAKE LEVERS	SRAM Rival AXS hydraulic
CASSETTE	SRAM Rival XPLR XG-1251, 12-speed, 10-44
CHAIN	SRAM Rival D1
CRANKSET	SRAM X-SYNC 46T BCD107 chain ring Praxis E Crank Alloy ISIS, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	Giant E+ System BBSS

WHEELS	
RIMS	Giant P-R2 Alloy Disc Wheel System, Tubeless Ready, 22mm inner width, 12mm thru-axle
SPOKES	Sapim spoke E-Light [R] Race [F], e-bike optimized
TYRES	Schwalbe G-one Allround Performance, RaceGuard, Brown side-wall, tubeless, 700x35
EXTRAS	N/A
LIMITS	
NSW CERTIFICATION	ULL-104279-EA
ACCESSORIES	
LIGHTING	Seatpost clamp integrated tail light
LIMITS	
MAX TYRE CLEARANCE	38mm

Price: $10,499.00

GEOMETRY

FRAME	S	M	ML	L
Seat Tube Length (mm)	445	480	515	535
Seat Post Insertion Depth (mm)	308	323	363	375
Seat Tube Angle	74.0°	73.5°	73.0°	73.0°
Top Tube Length (mm)	530	545	560	575
Head Tube Length (mm)	130	145	167	187
Head Tube Angle	71.5°	72.5°	72.5°	72.5°
Fork Rake (mm)	50	50	50	50
Trail (mm)	56.1	58.6	58.6	58.6
Wheelbase (mm)	994	995	1008	1023
Chain Stay Length (mm)	420	420	420	420
Bottom Bracket Drop (mm)	80	80	75	75
Stack (mm)	542	560	576	595
Reach (mm)	374	379	384	393
Stand Over Height (mm)	716	746	779	799
Stem Length (mm)	90	100	110	110
Wheel Size	700C	700C	700C	700C

*Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freighting and assembly costs.*