

DEFY ADVANCED E+ ELITE AR

GIANT



SPECS

HYBRID CYCLING TECHNOLOGY

MOTOR	SyncDriveMove Plus Hub drive 75Nm max
CONTROLLER	Mode support switch from SRAM Blips
DISPLAY	Giant RideControl GO, frame-integrated LED console Optional wireless ANT+ display
BATTERY	EnergyPak Smart 400Wh by Panasonic, Aluminium casing with highest safety standard (UL2271, EN50604), CO2 Neutral production, 2300 charging cycles. EnergyPak Plus 200 range extender compatible
CHARGER	Giant EnergyPak 4A smart charger, 60% in 1:45
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile

FRAME

SIZES	S, M, ML, L, XL
COLOURS	Matte Kelp Forest / Black
FRAME	Advanced-grade composite, 12x145 thru-axle
FORK	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
SHOCK	-

COMPONENTS

HANDLEBAR	Giant Contact SL D-Fuse 31.8 alloy
STEM	Contact SL Aerolight 31.8 alloy
SEATPOST	Giant D-Fuse, Composite, 14mm offset
SADDLE	Giant Approach
PEDALS	PEDALS NOT SUPPLIED

DRIVETRAIN

SHIFTERS	Sram Rival eTap AXS 1x12
FRONT DERAILLEUR	-
REAR DERAILLEUR	Sram Rival XPLR eTap AXS
BRAKES	Sram Rival eTap HRD, Paceline 160mm center-lock [F] 160mm 6-bols [R]
BRAKE LEVERS	Sram Rival eTap AXS HRD
CASSETTE	Sram Apex XPLR XG-1251, 10x44T, 12-speed
CHAIN	Sram Rival 12-speed
CRANKSET	Sram X-SYNC 46T BCD107 chain ring Praxis E Crank Carbon ISIS
BOTTOM BRACKET	Giant E+ System BBSS

WHEELS

RIMS	Giant P-X2 Alloy Disc Wheel System, Tubeless Ready, 19mm inner width, 12mm thru-axle, w/ Sapim spoke E-Light [R] Race [F], e-bike optimised
SPOKES	Sapim spoke E-Light [R] Race [F], e-bike optimised
TYRES	SCHWALBE G-ONE ALLROUND Perf, RaceGuard, Brown side-wall 700x35C 67EPI Tubeless

ACCESSORIES

LIGHTING	Seatpost clamp integrated tail light
-----------------	--------------------------------------

Price: €6,899.00

GEOMETRY

FRAME	ML
Seat Tube Length (mm)	515
Seat Tube Angle	73.0°
Top Tube Length (mm)	560
Head Tube Length (mm)	167
Head Tube Angle	72.5°
Fork Rake (mm)	50
Trail (mm)	58.6
Wheelbase (mm)	1007.5
Chain Stay Length (mm)	420
Bottom Bracket Drop (mm)	75
Stack (mm)	576.1
Reach (mm)	383.6
Stand Over Height (mm)	779
Handlebar Width (mm)	420
Stem Length (mm)	110
Crank Length (mm)	172.5
Wheel Size	700C

All specifications listed are subject to change without notice.