

DEFY ADVANCED E+ ELITE AR

GIANT



SPECS

HYBRID CYCLING TECHNOLOGY

MOTOR	SyncDriveMove Plus Hub drive 75Nm max
CONTROLLER	Mode support switch from SRAM Blips
DISPLAY	Giant RideControl GO, frame-integrated LED console Optional wireless ANT+ display
BATTERY	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
CHARGER	Giant EnergyPak smart charger 4A
CONNECTIVITY	Giant RideControl App enabled, ANT+ wireless display signal with e-bike profile

FRAME

SIZES	S, M, ML, L, XL
COLOURS	Mercury
FRAME	Advanced-grade composite, 12x145 thru-axle
FORK	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
SHOCK	-

COMPONENTS

HANDLEBAR	Giant Contact SL D-Fuse 31.8 alloy
STEM	Contact SL Aerolight 31.8 alloy
SEATPOST	Giant D-Fuse, Composite, 14mm offset
SADDLE	Giant Approach

DRIVETRAIN

SHIFTERS	Sram Rival AXS
FRONT DERAILLEUR	n/a
REAR DERAILLEUR	Sram Rival XPLR AXS
BRAKES	Sram Rival AXS HRD, Paceline 160mm 6-bols [F/R]
BRAKE LEVERS	Sram Rival AXS HRD
CASSETTE	Sram XPLR XG-1251 10x44T 12-speed
CHAIN	Sram Rival 12-speed
CRANKSET	Sram X-SYNC 46T BCD107 chain ring, Praxis E crank Alloy ISIS
BOTTOM BRACKET	Giant E+ System BBSS

WHEELS

RIMS	Giant P-R2 Alloy Disc Wheel System, Tubeless Ready, 22mm inner width, 12mm thru-axle
SPOKES	Sapim spoke E-Light [R] Race [F], e-bike optimized
TYRES	Schwalbe G-one Allround Performance, RaceGuard, Brown side-wall, tubeless, 700x35
EXTRAS	Fender adapter

ACCESSORIES

LIGHTING	Seatpost clamp integrated tail light
-----------------	--------------------------------------

Price: €6,599.00

GEOMETRY

FRAME	S	M	ML	L
Seat Tube Length (mm)	445	480	515	535
Seat Tube Angle	74.0°	73.5°	73.0°	73.0°
Top Tube Length (mm)	530	545	560	575
Head Tube Length (mm)	130	145	167	187
Head Tube Angle	71.5°	72.5°	72.5°	72.5°
Fork Rake (mm)	50	50	50	50
Trail (mm)	56.1	58.6	58.6	58.6
Wheelbase (mm)	994	995	1008	1023
Chain Stay Length (mm)	420	420	420	420
Bottom Bracket Drop (mm)	80	80	75	75
Stack (mm)	542	560	576	595
Reach (mm)	374	379	384	393
Stand Over Height (mm)	716	746	779	799
Handlebar Width (mm)	400	420	420	440
Stem Length (mm)	90	100	110	110
Wheel Size	700C	700C	700C	700C

All specifications listed are subject to change without notice.