

# DEFY ADVANCED E+ ELITE AR

**GIANT**

## SPECIFIKACIJE

HIBRIDNA TEHNOLOGIJA	
<b>MOTOR</b>	SyncDriveMove Plus Hub drive 75Nm max
<b>SENSOR</b>	Mode support switch from SRAM Blips
<b>PRIKAZ</b>	Giant RideControl GO, frame-integrated LED console Optional wireless ANT+ display
<b>BATERIJA</b>	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
<b>CHARGER</b>	Giant EnergyPak smart charger 4A
<b>CONNECTIVITY</b>	Giant RideControl App enabled, ANT+ wireless display signal with e-bike profile
OKVIR	
<b>VELIČINE</b>	S, M, ML, L, XL
<b>BOJE</b>	Mercury
<b>OKVIR</b>	Advanced-grade composite, 12x145 thru-axle
<b>VILICA</b>	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
<b>AMORTIZER</b>	-
KOMPONENTE	
<b>VOLAN</b>	Giant Contact SL D-Fuse 31.8 alloy
<b>LULA VOLANA</b>	Contact SL Aerolight 31.8 alloy
<b>CIJEV SJEDALA</b>	Giant D-Fuse, Composite, 14mm offset
<b>SJEDALO</b>	Giant Approach
POGON	
<b>RUČICE MJENJAČA</b>	Sram Rival AXS
<b>PREDNJI MJENJAČ</b>	n/a
<b>STRAŽNJI MJENJAČ</b>	Sram Rival XPLR AXS
<b>KOČNICE</b>	Sram Rival AXS HRD, Paceline 160mm 6-bols [F/R]
<b>RUČICE KOČNICA</b>	Sram Rival AXS HRD
<b>KAZETA</b>	Sram XPLR XG-1251 10x44T 12-speed
<b>LANAC</b>	Sram Rival 12-speed
<b>POGON</b>	Sram X-SYNC 46T BCD107 chain ring, Praxis E crank Alloy ISIS
<b>OSOVINA POGONA (BB)</b>	Giant E+ System BBSS

KOTAČI	
<b>OBRUČI</b>	Giant P-R2 Alloy Disc Wheel System, Tubeless Ready, 22mm inner width, 12mm thru-axle
<b>ŽBICE</b>	Sapim spoke E-Light [R] Race [F], e-bike optimized
<b>GUME</b>	Schwalbe G-one Allround Performance, RaceGuard, Brown side-wall, tubeless, 700x35
<b>DODACI</b>	Fender adapter
DODACI	
<b>SVJETLA</b>	Seatpost clamp integrated tail light

## GEOMETRIJA

OKVIR	S	M	ML	L	XL
Dužina cijevi sjedala (mm)	445	480	515	535	565
Kut cijevi sjedala	74,0°	73,5°	73,0°	73,0°	73,0°
Dužina gornje cijevi (mm)	530	545	560	575	590
Dužina prednje cijevi (mm)	130	145	167	187	205
Kut vilice	71,5°	72,5°	72,5°	72,5°	72,5°
Zakrivljenost vilice (offset) (mm)	50	50	50	50	50
Staza (mm)	56,1	58,6	58,6	58,6	58,6
Međuosovinski razmak kotača (mm)	994	995	1008	1023	1037,9
Dužina od osovine pogona do osovine zadnjeg kotača (CS) (mm)	420	420	420	420	420
Položaj osovine pogona (mm)	80	80	75	75	75
Vertikalna dužina od osovine pogona do glave okvira (stack) (mm)	542	560	576	595	612,4
Horizontalna dužina od osovine pogona do glave okvira (reach) (mm)	374	379	384	393	402,6
Prekoračna visina (mm)	716	746	779	799	824
Širina volana (mm)	400	420	420	440	440
Dužina lule volana (mm)	90	100	110	110	120
Veličina kotača	700C	700C	700C	700C	700C

Sve navedene specifikacije podložne su promjeni bez prethodne najave.