

DEFY ADVANCED E+ ELITE AR

GIANT



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTORE	SyncDriveMove Plus Hub drive 30 Nm (75 Nm effective)
COMANDO	Mode support switch from SRAM Blips
DISPLAY	Giant RideControl GO, frame-integrated LED console Optional wireless ANT+ display
BATTERIA	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
CARICATORE	Giant EnergyPak 4A smart charger, 60% in 1:45
CONNETTIVITÀ	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
TELAIO	
TAGLIE	S, M, ML, L, XL
COLORAZIONI	Kelp Forest / Black
TELAIO	Advanced-grade composite,12x145 thru-axle
FORCELLA	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
AMMORTIZZATORE	-
COMPONENTISTICA	
MANUBRIO	Giant Contact SL D-Fuse 31.8 alloy
ATTACCO MANUBRIO	Contact SL Aerolight 31.8 alloy
REGGISSELLA	Giant D-Fuse, Composite, 14mm offset
SELLA	Giant Approach.
SISTEMA DI TRASMISSIONE	
CAMBIO	Sram Rival eTap AXS
DERAGLIATORE ANTERIORE	-
DERAGLIATORE POSTERIORE	Sram Rival XPLR eTap AXS
FRENI	Sram Rival eTap HRD, Paceline 160mm center-lock [F] 160mm 6-bols [R]
COMANDI FRENO	Sram Rival eTap AXS HRD
PACCO PIGNONI	Sram Apex XPLR XG-1251, 10x44T, 12-speed
CATENA	Sram Rival 12-speed
GUARNITURA	Sram X-SYNC 46T BCD107 chain ring Praxis E Crank Alloy ISIS
MOVIMENTO CENTRALE	Giant E+ System BBSS

RUOTE	
CERCHI	Giant P-X2 Alloy Disc Wheel System, Tubeless Ready, 19mm inner width, 12mm thru-axle
RAGGI	Sapim spoke E-Light [R] Race [F], e-bike optimized
COPERTONI	SCHWALBE G-ONE ALLROUND Perf, RaceGuard, TLE 35-622, 28x1.35 700x35C, B/BRZ-SK HS473 ADDIX 67EPI
ACCESSORI	
ILLUMINAZIONE	Seatpost clamp integrated tail light

Prezzo: 5.999,00 €

GEOMETRIA

TELAIO	S	M	L	XL
Lunghezza Tubo Sella (mm)	445	480	535	565
Angolo Tubo Sella	74,0°	73,5°	73,0°	73,0°
Lunghezza Tubo Orizzontale (mm)	530	545	575	590
Lunghezza Tubo Sterzo (mm)	130	145	187	205
Angolo Sterzo	71,5°	72,5°	72,5°	72,5°
Rake Forcella (mm)	50	50	50	50
Avancorsa (mm)	65,1	58,6	58,6	58,6
Interasse (mm)	994,3	995,2	1022,7	1037,9
Lunghezza Carro Posteriore (mm)	420	420	420	420
Drop Movimento Centrale (mm)	80	80	75	75
Stack (mm)	542,2	560,2	595,2	612,4
Reach (mm)	374,3	378,9	392,8	402,6
Altezza stand over (mm)	716	745,5	799	824
Larghezza Manubrio c/c (mm)	400	420	440	440
Lunghezza Attacco Manubrio (mm)	90	100	110	120
Lunghezza Pedivella (mm)	170	172,5	175	175
Dimensione Ruote	700C	700C	700C	700C

Le specifiche tecniche e i colori sono soggette a variazioni senza obbligo di preavviso. Verifica la disponibilità con il tuo rivenditore Giant e Liv di fiducia.