

# DEFY ADVANCED E+ ELITE AR

**GIANT**



## SPECS

HYBRID CYCLING TECHNOLOGY	
<b>MOTOR</b>	SyncDriveMove Plus Hub drive 75Nm max
<b>SENSOR</b>	Mode support switch from SRAM Blips
<b>DISPLAY</b>	Giant RideControl GO, frame-integrated LED console Optional wireless ANT+ display
<b>BATTERY</b>	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
<b>CHARGER</b>	Giant EnergyPak smart charger 4A
<b>CONNECTIVITY</b>	Giant RideControl App enabled, ANT+ wireless display signal with e-bike profile
CADRU	
<b>MARIMI</b>	S, M, ML, L, XL
<b>CULORI</b>	Mercury
<b>CADRU</b>	Advanced-grade composite, 12x145 thru-axle
<b>FURCA</b>	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
<b>SOC</b>	-
COMPONENTE	
<b>GHIDON</b>	Giant Contact SL D-Fuse 31.8 alloy
<b>PIPA</b>	Contact SL Aerolight 31.8 alloy
<b>TIJA SA</b>	Giant D-Fuse, Composite, 14mm offset
<b>SA</b>	Giant Approach
SISTEMUL DE SCHIMBARE A VITEZELOR	
<b>MANETE SCHIMBATOR</b>	Sram Rival AXS
<b>SCHIMBATOR FATA</b>	n/a
<b>SCHIMBATOR SPATE</b>	Sram Rival XPLR AXS
<b>FRANE</b>	Sram Rival AXS HRD, Paceline 160mm 6-bols [F/R]
<b>MANETE FRANA</b>	Sram Rival AXS HRD
<b>PINIOANE</b>	Sram XPLR XG-1251 10x44T 12-speed
<b>LANT</b>	Sram Rival 12-speed
<b>ANGRENAJ</b>	Sram X-SYNC 46T BCD107 chain ring, Praxis E crank Alloy ISIS
<b>BOTTOM BRACKET</b>	Giant E+ System BBSS

ROTI	
<b>JANTE</b>	Giant P-R2 Alloy Disc Wheel System, Tubeless Ready, 22mm inner width, 12mm thru-axle
<b>SPITE</b>	Sapim spoke E-Light [R] Race [F], e-bike optimized
<b>ANVELOPE</b>	Schwalbe G-one Allround Performance, RaceGuard, Brown side-wall, tubeless, 700x35
<b>EXTRAS</b>	Fender adapter
ACCESSORIES	
<b>LIGHTING</b>	Seatpost clamp integrated tail light

## GEOMETRIE

CADRU	S	M	ML	L	XL
Seat Tube Length (mm)	445	480	515	535	565
Seat Tube Angle	74,0°	73,5°	73,0°	73,0°	73,0°
Top Tube Length (mm)	530	545	560	575	590
Head Tube Length (mm)	130	145	167	187	205
Head Tube Angle	71,5°	72,5°	72,5°	72,5°	72,5°
Fork Rake (mm)	50	50	50	50	50
Trail (mm)	56,1	58,6	58,6	58,6	58,6
Wheelbase (mm)	994	995	1008	1023	1037,9
Chain Stay Length (mm)	420	420	420	420	420
Bottom Bracket Drop (mm)	80	80	75	75	75
Stack (mm)	542	560	576	595	612,4
Reach (mm)	374	379	384	393	402,6
Stand Over Height (mm)	716	746	779	799	824
Handlebar Width (mm)	400	420	420	440	440
Stem Length (mm)	90	100	110	110	120
Wheel Size	700C	700C	700C	700C	700C

Toate specificatiile enumerate se pot schimba fara notificare prealabila.