

DEFY ADVANCED E+ ELITE AR

GIANT

ŠPECIFIKÁCIE

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDriveMove Plus Hub drive 75Nm max
OVLÁDAČ	Mode support switch from SRAM Blips
OVLÁDACIA JEDNOTKA	Giant RideControl GO, frame-integrated LED console Optional wireless ANT+ display
BATÉRIA	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
NABÍJAČKA	Giant EnergyPak smart charger 4A
KONEKTIVITA	Giant RideControl App enabled, ANT+ wireless display signal with e-bike profile
RÁM	
VELKOSTI	S, M, ML, L, XL
FARBY	Mercury
RÁM	Advanced-grade composite, 12x145 thru-axle
VIDLICA	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
TLMÍČ	-
KOMPONENTY	
RIADIDLÁ	Giant Contact SL D-Fuse 31.8 alloy
PREDSTAVEC	Contact SL Aerolight 31.8 alloy
SEDOVKA	Giant D-Fuse, Composite, 14mm offset
SEDADLO	Giant Approach
POHON	
RADENIE	Sram Rival AXS
PREŠMYKAČ	n/a
PREHADZOVAČKA	Sram Rival XPLR AXS
BRZDY	Sram Rival AXS HRD, Paceline 160mm 6-bols [F/R]
BRZDOVÉ PÁKY	Sram Rival AXS HRD
KAZETA	Sram XPLR XG-1251 10x44T 12-speed
REŤAZ	Sram Rival 12-speed
KLUKY	Sram X-SYNC 46T BCD107 chain ring, Praxis E crank Alloy ISIS
STREDOVÉ ZLOŽENIE	Giant E+ System BBSS

KOLESÁ	
RÁFIKY	Giant P-R2 Alloy Disc Wheel System, Tubeless Ready, 22mm inner width, 12mm thru-axle
ŠPICE	Sapim spoke E-Light [R] Race [F], e-bike optimized
PNEUMATIKY	Schwalbe G-one Allround Performance, RaceGuard, Brown side-wall, tubeless, 700x35
DOPLNKY	Fender adapter
PRÍSLUŠENSTVO	
OSVETLENIE	Seatpost clamp integrated tail light

Cena: 6 599 €

GEOMETRIA

RÁM	S	M	ML	L	XL
Dĺžka sedlovej trubky (mm)	445	480	515	535	565
Uhol sedlovej trubky	74,0°	73,5°	73,0°	73,0°	73,0°
Dĺžka hornej rámovej trubky (mm)	530	545	560	575	590
Dĺžka hlavovej trubky (mm)	130	145	167	187	205
Uhol hlavovej trubky	71,5°	72,5°	72,5°	72,5°	72,5°
Offset vidlice (mm)	50	50	50	50	50
Trail (mm)	56,1	58,6	58,6	58,6	58,6
Rázvor (mm)	994	995	1008	1023	1037,9
Dĺžka zadnej stavby (mm)	420	420	420	420	420
Rozdiel zadnej voči stredovej osi - BB DROP (mm)	80	80	75	75	75
Stack - výška riadenia (mm)	542	560	576	595	612,4
Reach (mm)	374	379	384	393	402,6
Výška rámu od zeme (mm)	716	746	779	799	824
Šírka riaditok (mm)	400	420	420	440	440
Dĺžka predstavca (mm)	90	100	110	110	120
Rozmer kolies	700C	700C	700C	700C	700C

Všetky ceny a špecifikácie sa môžu zmeniť bez predchádzajúceho upozornenia.