

DEFY ADVANCED E+ ELITE AR

GIANT



SPECIFIKACIJE

HIBRIDNA GONILNA TEHNOLOGIJA	
MOTOR	SyncDriveMove Plus Hub drive 75Nm max
TIPALO	Mode support switch from SRAM Blips
PRIKAZOVALNIK	Giant RideControl GO, frame-integrated LED console Optional wireless ANT+ display
BATERIJA	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
CHARGER	Giant EnergyPak smart charger 4A
CONNECTIVITY	Giant RideControl App enabled, ANT+ wireless display signal with e-bike profile
OKVIR	
VELIKOSTI	S, M, ML, L, XL
BARVE	Mercury
OKVIR	Advanced-grade composite, 12x145 thru-axle
VILICE	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
AMORTIZER	-
KOMPONENTE	
KRMILO	Giant Contact SL D-Fuse 31.8 alloy
OPORA KRMILA	Contact SL Aerolight 31.8 alloy
OPORA SEDEŽA	Giant D-Fuse, Composite, 14mm offset
SEDEŽ	Giant Approach
POGON	
PRESTAVNE ROČICE	Sram Rival AXS
PREDNJI MENJALNIK	n/a
ZADNJI MENJALNIK	Sram Rival XPLR AXS
ZAVORE	Sram Rival AXS HRD, Paceline 160mm 6-bols [F/R]
ZAVORNE ROČICE	Sram Rival AXS HRD
VERIŽNIK	Sram XPLR XG-1251 10x44T 12-speed
VERIGA	Sram Rival 12-speed
GONILKE Z VERIŽNIKI	Sram X-SYNC 46T BCD107 chain ring, Praxis E crank Alloy ISIS
BOTTOM BRACKET	Giant E+ System BBSS

OBROČNIKI	
OBROČI	Giant P-R2 Alloy Disc Wheel System, Tubeless Ready, 22mm inner width, 12mm thru-axle
NAPERE	Sapim spoke E-Light [R] Race [F], e-bike optimized
PLAŠČI	Schwalbe G-one Allround Performance, RaceGuard, Brown side-wall, tubeless, 700x35
DODATKI	Fender adapter
DODATNA OPREMA	
SVETILA	Seatpost clamp integrated tail light

GEOMETRIJA

OKVIR	S	M	ML	L	XL
Dolžina sedežne cevi (mm)	445	480	515	535	565
Kot sedežne cevi	74,0°	73,5°	73,0°	73,0°	73,0°
Top Tube Length (mm)	530	545	560	575	590
Višina glave okvirja (mm)	130	145	167	187	205
Krmlini kot	71,5°	72,5°	72,5°	72,5°	72,5°
Zamik vpetja osi (mm)	50	50	50	50	50
Trail (mm)	56,1	58,6	58,6	58,6	58,6
Medosna razdalja (mm)	994	995	1008	1023	1037,9
Dolžina cevi ob verigi (mm)	420	420	420	420	420
Bottom Bracket Drop (mm)	80	80	75	75	75
Oddaljenost zgornje cevi od gonilne osi (mm)	542	560	576	595	612,4
Doseg (mm)	374	379	384	393	402,6
Višina zgornje cevi (mm)	716	746	779	799	824
Širina krmila (mm)	400	420	420	440	440
Dolžina opore krmila (mm)	90	100	110	110	120
Velikost obročnikov	700C	700C	700C	700C	700C

Vse navedene specifikacije se lahko spremenijo brez obvestila.