

# DEFY ADVANCED PRO 0-AXS



## SPEZIFIKATIONEN

| RAHMEN & GABEL     |                                                                                                             |
|--------------------|-------------------------------------------------------------------------------------------------------------|
| RAHMENGRÖSSEN      | XS, S, M, M/L, L, XL                                                                                        |
| FARBE(N)           | Luminous Lagoon                                                                                             |
| RAHMEN             | Advanced-grade Composite, 12x142mm thru-axle, disc                                                          |
| GABEL              | Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc                |
| COCKPIT            |                                                                                                             |
| LENKER             | Giant Contact SLR D-Fuse XS:404/380mm, S:404/380mm, M:424/400mm, M/L:424/400mm, L:444/420mm, XL:444/420mm   |
| GRIFFE             | Stratus Lite 3.0                                                                                            |
| VORBAU             | Giant Contact SL AeroLight XS:80mm, S:90mm, M:100mm, M/L:100mm, L:110mm, XL:110mm                           |
| SATTELSTÜTZE       | Giant D-Fuse SLR, composite, -5/+15mm offset                                                                |
| SATTEL             | Giant Fleet SL                                                                                              |
| SCHALTUNG, ANTRIEB |                                                                                                             |
| SCHALTHEBEL        | Sram Force AXS E1                                                                                           |
| UMWERFER           | Sram Force AXS E1                                                                                           |
| SCHALTWERK         | Sram Force AXS E1                                                                                           |
| BREMSEN            | SRAM Force AXS E1 hydraulic, SRAM CenterLine X rotors [F]160mm, [R]160mm                                    |
| BREMSEHEBEL        | SRAM Force AXS E1 hydraulic                                                                                 |
| KASSETTE           | Sram Force E1, 12-speed, 10-36 XG-1270-E1                                                                   |
| KETTE              | Sram Force E1, 12-speed                                                                                     |
| KURBELSATZ         | Sram Force E1 DUB,33/46 with power meter XS: 165mm, S: 165mm, M: 170mm, M/L: 170mm, L: 172.5mm, XL: 172.5mm |

| LAUFRÄDER                |                                                                                                                                   |
|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------|
| FELGEN                   | Giant SLR 0 40 Carbon Disc WheelSystem                                                                                            |
| NABEN (V/H)              | [F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 40T ratchet driver, CenterLock, 12mm thru-axle |
| SPEICHEN                 | Aero Carbon                                                                                                                       |
| REIFEN                   | CADEX Classics, tubeless, 700x32c (33.5mm), folding                                                                               |
| ZUBEHÖR (TEILW. VERBAUT) | computer mount, fender mount, water bottle cages, tubeless prepared                                                               |
| GRENZEN                  |                                                                                                                                   |
| MAX. REIFENBREITE        | 40mm                                                                                                                              |

UVP: 6.500,00 €

## GEOMETRIEDATEN

| RAHMEN & GABEL                      | S     | M     | ML    | L     | XL    |
|-------------------------------------|-------|-------|-------|-------|-------|
| Sitzrohrlänge (mm)                  | 445   | 480   | 515   | 535   | 565   |
| Einstecktiefe der Sattelstütze (mm) | 190   | 190   | 190   | 190   | 190   |
| Sitzwinkel                          | 74,0° | 73,5° | 73,0° | 73,0° | 73,0° |
| Oberrohrlänge (mm)                  | 530   | 545   | 560   | 575   | 595   |
| Steuerrohrlänge (mm)                | 135   | 150   | 175   | 195   | 215   |
| Lenkwinkel                          | 71,8° | 72,5° | 72,5° | 72,5° | 72,5° |
| Gabelvorbiegung (mm)                | 50    | 50    | 50    | 50    | 50    |
| Gabelnachlauf (mm)                  | 63,4  | 58,6  | 58,6  | 58,6  | 58,6  |
| Radstand (mm)                       | 994   | 998   | 1010  | 1025  | 1040  |
| Kettenstrebenlänge (mm)             | 420   | 420   | 420   | 420   | 420   |
| Tretlagerabsenkung (mm)             | 75    | 75    | 70    | 70    | 70    |
| Stack (mm)                          | 541   | 558   | 577   | 596   | 615   |
| Reach (mm)                          | 375   | 380   | 384   | 393   | 402   |
| Überstands-/Durchstiegshöhe (mm)    | 733   | 762   | 796   | 814   | 841   |
| Lenkerbreite (mm)                   | 404   | 424   | 424   | 444   | 444   |
| Vorbaulänge (mm)                    | 90    | 100   | 100   | 110   | 110   |
| Kurbelarmlänge (mm)                 | 165   | 170   | 170   | 172,5 | 172,5 |

Spezifikations-, Preis- und Farbänderungen vorbehalten.