

DEFY ADVANCED PRO 0-AXS



產品規格

車架	
尺寸	XS, S, M, M/L,
顏色	藍
車架	Advanced-grade Composite, 12x142mm thru-axle, disc
前叉	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
COMPONENTS	
車把手	Giant Contact SLR D-Fuse XS:404/380mm, S:404/380mm, M:424/400mm, M/L:424/400m
把手帶/套	Stratus Lite 3.0
豎桿	Giant Contact SL AeroLight XS:80mm, S:90mm, M:100mm, M/L:100mm
座桿	Giant D-Fuse SLR, composite, -5/+15mm offset
坐墊	Giant Fleet SL
DRIVETRAIN	
變速把手	Sram Force AXS E1
前變速器	Sram Force AXS E1
後變速器	Sram Force AXS E1
煞車系統	SRAM Force AXS E1 hydraulic, SRAM CenterLine X rotors [F]160mm, [R]160mm
煞車把手	SRAM Force AXS E1 hydraulic
飛輪	Sram Force E1, 12-speed, 10-36 XG-1270-E1
鏈條	Sram Force E1, 12-speed
大齒盤	Sram Force E1 DUB,33/46 with power meter XS: 165mm, S: 165mm, M: 170mm, M/L: 170mm,

輪組	
輪圈	Giant SLR 0 40 Carbon Disc WheelSystem
花鼓	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 40T ratchet driver, CenterLock, 12mm thru-axle
輻條	Aero Carbon
外胎	CADEX Classics, tubeless, 700x32c (33.5mm), folding
其他	computer mount, fender mount, water bottle cages, tubeless prepared
LIMITS	
MAX TIRE CLEARANCE	40mm

Price: NT\$168,000

車架幾何

車架	XS	S	M	ML
座(立)管長 (mm)	410	445	480	515
座(立)管角度	74.5°	74.0°	73.5°	73.0°
上管長度 (mm)	515	530	545	560
頭管長度 (mm)	125	135	150	175
頭管角度	70.5°	71.8°	72.5°	72.5°
前叉 (mm)	50	50	50	50
Trail (mm)	71.6	63.4	58.6	58.6
前後輪距 (mm)	995	994	998	1010
後下叉長度 (mm)	420	420	420	420
五通下降高度 (mm)	75	75	75	70
頭碗至五通高度 (mm)	527	541	558	577
頭碗至五通長度 (mm)	369	375	380	384
上管至地面高度 (mm)	705	733	762	796
把手寬 (mm)	404	404	424	424
龍頭長度 (mm)	80	90	100	100
曲柄長度 (mm)	165	165	170	170

* 捷安特公司對本網站所刊載之產品資料保留修改權利，恕不另行通知(包括有關設備、規格、型號、重量、顏色和材料等)，請以實際產品為主。