

# DEFY ADVANCED PRO 0

GIANT



## SPECIFIKATIONER

RAMME	
STØRRELSER	S, M, M/L, L, XL
FARVER	Mariana Blue
RAMME	Advanced-grade Composite, 12x142mm thru-axle, disc
FORGAFFEL	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
KOMPONENTER	
STYR	Giant Contact SLR D-Fuse XS:404/380mm, S:404/380mm, M:424/400mm, M/L:424/400mm, L:444/420mm, XL:444/420mm
GREB / STYRBÅND	Stratus Lite 3.0
FREMPIND	Giant Contact SL AeroLight XS:80mm, S:90mm, M:100mm, M/L:100mm, L:110mm, XL:110mm
SADELPIND	Giant D-Fuse SLR, composite, -5/+15mm offset
SADEL	Giant Fleet SL
GEARGRUPPE	
SKIFTEGREB	Shimano Ultegra Di2 ST-R8170
FORSKIFTER	Shimano Ultegra Di2 FD-R8150
BAGSKIFTER	Shimano Ultegra Di2 RD-R8150
BREMSE	Shimano Ultegra Di2 hydraulic, Shimano RT-CL800 rotors [F]160mm, [R]160mm
BREMSEGREB	Shimano Ultegra Di2
KASSETTE	Shimano Ultegra, 12-speed, 11x34
KÆDE	Shimano Ultegra
KRANKSÆT	Shimano Ultegra, 34/50 with Giant Power Pro power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
KRANKBOKS	Shimano, press fit

HJUL	
FÆLGE	Giant SLR 0 40 Carbon Disc WheelSystem
NAV	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 40T ratchet driver, CenterLock, 12mm thru-axle
EGER	Aero Carbon
DÆK	CADEX Classics, tubeless, 700x32c (33.5mm), folding
EKSTRA	computer mount, fender mount, water bottle cages, tubeless prepared, 40mm max tire size
GRÆNSER	
MAX DÆKSTØRRELSE	40mm

Pris: 52.299,00 kr.

## GEOMETRI

RAMME	S	M	ML	L	XL
Sadelrørlængde (mm)	445	480	515	535	565
Sadelrørvinkel	74,0°	73,5°	73,0°	73,0°	73,0°
Overrørlængde (mm)	530	545	560	575	595
Kronrørlængde (mm)	135	150	175	195	215
Kronrørvinkel	71,8°	72,5°	72,5°	72,5°	72,5°
Forgaffel fremspring (rake) (mm)	50	50	50	50	50
Sti (mm)	63,4	58,6	58,6	58,6	58,6
Akselafstand (mm)	994	998	1010	1025	1040
Kædestagslængde (mm)	420	420	420	420	420
Krankboks drop (mm)	75	75	70	70	70
Stack (mm)	541	558	577	596	615
Reach (mm)	375	380	384	393	402
Skridthøjde (mm)	733	762	796	814	841
Styrbredde (mm)	404	424	424	444	444
Frempindslængde (mm)	90	100	100	110	110
Pedalarmslængde (mm)	165	170	170	172,5	172,5

Alle de anførte specifikationer kan ændres uden varsel.