

DEFY ADVANCED PRO 0

GIANT



SPECS

| FRAME | |
|-------------------------|--|
| SIZES | S, M, M/L, L, XL |
| COLOURS | Mariana Blue |
| FRAME | Advanced-grade Composite, 12x142mm thru-axle, disc |
| FORK | Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc |
| COMPONENTS | |
| HANDLEBAR | Giant Contact SLR D-Fuse XS:404/380mm, S:404/380mm, M:424/400mm, M/L:424/400mm, L:444/420mm, XL:444/420mm |
| GRIPS | Stratus Lite 3.0 |
| STEM | Giant Contact SL AeroLight XS:80mm, S:90mm, M:100mm, M/L:100mm, L:110mm, XL:110mm |
| SEATPOST | Giant D-Fuse SLR, composite, -5/+15mm offset |
| SADDLE | Giant Fleet SL |
| PEDALS | PEDALS NOT SUPPLIED |
| DRIVETRAIN | |
| SHIFTERS | Shimano Ultegra Di2 ST-R8170 |
| FRONT DERAILLEUR | Shimano Ultegra Di2 FD-R8150 |
| REAR DERAILLEUR | Shimano Ultegra Di2 RD-R8150 |
| BRAKES | Shimano Ultegra Di2 hydraulic, Shimano RT-CL800 rotors [F]160mm, [R]160mm |
| BRAKE LEVERS | Shimano Ultegra Di2 |
| CASSETTE | Shimano Ultegra, 12-speed, 11x34 |
| CHAIN | Shimano Ultegra |
| CRANKSET | Shimano Ultegra, 34/50 with Giant Power Pro power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm |
| BOTTOM BRACKET | Shimano, press fit |

| WHEELS | |
|---------------------------|---|
| RIMS | Giant SLR 0 40 Carbon Disc WheelSystem |
| HUBS | [F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 40T ratchet driver, CenterLock, 12mm thru-axle |
| SPOKES | Aero Carbon |
| TYRES | CADEX Classics, tubeless, 700x32c (33.5mm), folding |
| EXTRAS | computer mount, fender mount, water bottle cages, tubeless prepared, 40mm max tire size |
| LIMITS | |
| MAX TYRE CLEARANCE | 40mm |

Price: £5,499.00

GEOMETRY

| FRAME | S | M | ML | L | XL |
|--------------------------|-------|-------|-------|-------|-------|
| Seat Tube Length (mm) | 445 | 480 | 515 | 535 | 565 |
| Seat Tube Angle | 74.0° | 73.5° | 73.0° | 73.0° | 73.0° |
| Top Tube Length (mm) | 530 | 545 | 560 | 575 | 595 |
| Head Tube Length (mm) | 135 | 150 | 175 | 195 | 215 |
| Head Tube Angle | 71.8° | 72.5° | 72.5° | 72.5° | 72.5° |
| Fork Rake (mm) | 50 | 50 | 50 | 50 | 50 |
| Trail (mm) | 63.4 | 58.6 | 58.6 | 58.6 | 58.6 |
| Wheelbase (mm) | 994 | 998 | 1010 | 1025 | 1040 |
| Chain Stay Length (mm) | 420 | 420 | 420 | 420 | 420 |
| Bottom Bracket Drop (mm) | 75 | 75 | 70 | 70 | 70 |
| Stack (mm) | 541 | 558 | 577 | 596 | 615 |
| Reach (mm) | 375 | 380 | 384 | 393 | 402 |
| Stand Over Height (mm) | 733 | 762 | 796 | 814 | 841 |
| Handlebar Width (mm) | 404 | 424 | 424 | 444 | 444 |
| Stem Length (mm) | 90 | 100 | 100 | 110 | 110 |
| Crank Length (mm) | 165 | 170 | 170 | 172.5 | 172.5 |

Every effort has been made to ensure accuracy throughout this website. However, Giant reserves the right to change bike specifications, features, prices and colours without prior notice.