

DEFY ADVANCED PRO 0



SPECS

FRAME	
SIZES	XS, S, M, M/L, L, XL
COLORS	Luminous Lagoon/Chrome
FRAME	Advanced-grade composite, 12x142mm thru-axle, disc
FORK	Advanced SL-grade composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
COMPONENTS	
HANDLEBAR	Giant Contact SLR D-Fuse XS:404/380mm, S:404/380mm, M:424/400mm, M/L:424/400mm, L:444/420mm, XL:444/420mm
GRIPS	Stratus Lite 3.0
STEM	Giant Contact SL AeroLight XS:80mm, S:90mm, M:100mm, M/L:100mm, L:110mm, XL:110mm
SEATPOST	Giant D-Fuse SLR, composite, -5/+15mm offset
SADDLE	Giant Fleet SL
PEDALS	platform pedal [GCS,GTS] / N/A [all other GSC]
DRIVETRAIN	
SHIFTERS	Shimano Ultegra Di2 ST-R8170
FRONT DERAILLEUR	Shimano Ultegra Di2 FD-R8150
REAR DERAILLEUR	Shimano Ultegra Di2 RD-R8150
BRAKES	Shimano Ultegra hydraulic, Shimano RT-CL800 rotors [F]160mm, [R]160mm
BRAKE LEVERS	Shimano Ultegra Di2
CASSETTE	Shimano Ultegra, 12-speed, 11x34
CHAIN	Shimano Ultegra
CRANKSET	Shimano Ultegra, 34/50 with Giant Power Pro power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
BOTTOM BRACKET	Shimano, press fit

WHEELS	
RIMS	Giant SLR 0 40 Carbon Disc WheelSystem
HUBS	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle / [R] Giant Low Friction Hub, 40T ratchet driver, CenterLock, 12mm thru-axle
SPOKES	Sapim
TIRES	CADEX Classic, tubeless, 700x32c (33.5mm), folding
EXTRAS	computer mount, fender mount, water bottle cages, tubeless prepared, 40mm max tire size

Price: \$8,699.00

GEOMETRY

FRAME	XS	S	M	ML	L	XL
Seat Tube Length (mm)	410	445	480	515	535	565
Seat Post Insertion Depth (mm)	190	190	190	190	190	190
Seat Tube Angle	74.5°	74.0°	73.5°	73.0°	73.0°	73.0°
Top Tube Length (mm)	515	530	545	560	575	595
Head Tube Length (mm)	125	135	150	175	195	215
Head Tube Angle	70.5°	71.8°	72.5°	72.5°	72.5°	72.5°
Fork Rake (mm)	50	50	50	50	50	50
Trail (mm)	71.6	63.4	58.6	58.6	58.6	58.6
Wheelbase (mm)	995	994	998	1010	1025	1040
Chain Stay Length (mm)	420	420	420	420	420	420
Bottom Bracket Drop (mm)	75	75	75	70	70	70
Stack (mm)	527	541	558	577	596	615
Reach (mm)	369	375	380	384	393	402
Stand Over Height (mm)	705	733	762	796	814	841
Stem Length (mm)	80	90	100	100	110	110
Crank Length (mm)	165	165	170	170	172.5	172.5

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.