

DEFY ADVANCED PRO 0



TEKNISET TIEDOT

RUNKO	
KOOT	S, M, M/L, L, XL
VÄRIT	Luminous Lagoon/Chrome
RUNKO	Advanced-grade composite, 12x142mm thru-axle, disc
HAARUKKA	Advanced SL-grade composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
KOMPONENTIT	
OHJAUSTANKO	Giant Contact SLR D-Fuse XS:404/380mm, S:404/380mm, M:424/400mm, M/L:424/400mm, L:444/420mm, XL:444/420mm
GRIPIT	Stratus Lite 3.0
OHJAINKANNATIN	Giant Contact SL AeroLight XS:80mm, S:90mm, M:100mm, M/L:100mm, L:110mm, XL:110mm
SATULATOLPPA	Giant D-Fuse SLR, composite, -5/+15mm offset
SATULA	Giant Fleet SL
POLKIMET	platform pedal [GCS,GTS] / N/A [all other GSC]
VOIMANSIIRTO	
VAIHDEVIPU	Shimano Ultegra Di2 ST-R8170
ETUVAIHTAJA	Shimano Ultegra Di2 FD-R8150
TAKAVAIHTAJA	Shimano Ultegra Di2 RD-R8150
JARRUT	Shimano Ultegra hydraulic, Shimano RT-CL800 rotors [F]160mm, [R]160mm
JARRUKAHVAT	Shimano Ultegra Di2
RATASPAKKA	Shimano Ultegra, 12-speed, 11x34
KETJUT	Shimano Ultegra
KAMPISARJA	Shimano Ultegra, 34/50 with Giant Power Pro power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
KESKIÖ	Shimano, press fit

RENKAAT	
VANTEET	Giant SLR 0 40 Carbon Disc WheelSystem
NAVAT	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle / [R] Giant Low Friction Hub, 40T ratchet driver, CenterLock, 12mm thru-axle
PINNAT	Sapim
RENKAAT	CADEX Classic, tubeless, 700x32c (33.5mm), folding
LISÄTIEDOT	computer mount, fender mount, water bottle cages, tubeless prepared, 40mm max tire size

Suositusuhinta: 6 909,00 €

GEOMETRIA

RUNKO	S	M	ML	L	XL
Satulaputken pituus (mm)	445	480	515	535	565
Satulatolpan asennussyvyys (mm)	190	190	190	190	190
Satulaputken kulma	74,0°	73,5°	73,0°	73,0°	73,0°
Vaakaputken pituus (mm)	530	545	560	575	595
Emäputken pituus (mm)	135	150	175	195	215
Emäputken kulma	71,8°	72,5°	72,5°	72,5°	72,5°
Haarukan offset (mm)	50	50	50	50	50
Trail-mitta (mm)	63,4	58,6	58,6	58,6	58,6
Akseliväli (mm)	994	998	1010	1025	1040
Takahaarukan alaputken pituus (mm)	420	420	420	420	420
Keskiön pudotus (mm)	75	75	70	70	70
Stack-mitta (mm)	541	558	577	596	615
Reach-mitta (mm)	375	380	384	393	402
Standover-mitta (mm)	733	762	796	814	841
Ohjaustangon leveys (mm)	404	424	424	444	444
Ohjainkannattimen pituus (mm)	90	100	100	110	110
Kammen pituus (mm)	165	170	170	172,5	172,5

Kaikki ilmoitetut tekniset tiedot voivat muuttua ilman erillistä ilmoitusta.