

DEFY ADVANCED PRO 0

GIANT



SPECIFICATIES

FRAME	
MATEN	S, M, M/L, L, XL
KLEUREN	Luminous Lagoon/Chrome
FRAME	Advanced-grade composite, 12x142mm thru-axle, disc
VOORVORK	Advanced SL-grade composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
ONDERDELEN	
STUUR	Giant Contact SLR D-Fuse XS:404/380mm, S:404/380mm, M:424/400mm, M/L:424/400mm, L:444/420mm, XL:444/420mm
HANDVATTEN	Stratus Lite 3.0
STUURPEN	Giant Contact SL AeroLight XS:80mm, S:90mm, M:100mm, M/L:100mm, L:110mm, XL:110mm
ZADELPEN	Giant D-Fuse SLR, composite, -5/+15mm offset
ZADEL	Giant Fleet SL
PEDALEN	platform pedal [GCS,GTS] / N/A [all other GSC]
AFMONTAGE	
SHIFTERS	Shimano Ultegra Di2 ST-R8170
VOORDERAILLEUR	Shimano Ultegra Di2 FD-R8150
ACHTERDERAILLEUR	Shimano Ultegra Di2 RD-R8150
REMMEN	Shimano Ultegra hydraulic, Shimano RT-CL800 rotors [F]160mm, [R]160mm
REMHENDELS	Shimano Ultegra Di2
CASSETTE	Shimano Ultegra, 12-speed, 11x34
AANDRIJVING	Shimano Ultegra
CRANKSET	Shimano Ultegra, 34/50 with Giant Power Pro power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
BOTTOM BRACKET	Shimano, press fit

WIELSET	
VELGEN	Giant SLR 0 40 Carbon Disc WheelSystem
NAVEN	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle / [R] Giant Low Friction Hub, 40T ratchet driver, CenterLock, 12mm thru-axle
SPAKEN	Sapim
BANDEN	CADEX Classic, tubeless, 700x32c (33.5mm), folding
EXTRA'S	computer mount, fender mount, water bottle cages, tubeless prepared, 40mm max tire size

Adviesprijs: € 6.499,00

GEOMETRIE

FRAME	S	M	ML	L	XL
Zitbuis Lengte (mm)	445	480	515	535	565
Seat Post Insertion Depth (mm)	190	190	190	190	190
Zitbuis Hoek	74,0°	73,5°	73,0°	73,0°	73,0°
Frame Lengte (horizontaal) (mm)	530	545	560	575	595
Balhoofdbuis Lengte (mm)	135	150	175	195	215
Balhoofdbuis Hoek	71,8°	72,5°	72,5°	72,5°	72,5°
Vork Sprong (mm)	50	50	50	50	50
Naloop (mm)	63,4	58,6	58,6	58,6	58,6
Wielbasis (mm)	994	998	1010	1025	1040
Liggende achtervork lengte (mm)	420	420	420	420	420
Bottom Bracket Drop (mm)	75	75	70	70	70
Stack (mm)	541	558	577	596	615
Reach (mm)	375	380	384	393	402
Stand Over Height (mm)	733	762	796	814	841
Stuur breedte (mm)	404	424	424	444	444
Stuurpen Lengte (mm)	90	100	100	110	110
Cranklengte (mm)	165	170	170	172,5	172,5

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.