

DEFY ADVANCED PRO 0



CARACTÉRISTIQUES TECHNIQUES

CADRE	
TAILLES	XS, S, M, M/L, L, XL
COLORIS	Mariana Blue
CADRE	Advanced-grade Composite, 12x142mm thru-axle, disc
FOURCHE	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
COMPOSANTS	
CINTRE	Giant Contact SLR D-Fuse XS:404/380mm, S:404/380mm, M:424/400mm, M/L:424/400mm, L:444/420mm, XL:444/420mm
POIGNÉES	Stratus Lite 3.0
POTENCE	Giant Contact SL AeroLight XS:80mm, S:90mm, M:100mm, M/L:100mm, L:110mm, XL:110mm
TIGE DE SELLE	Giant D-Fuse SLR, composite, -5/+15mm offset
SELLE	Giant Fleet SL
DÉRAILLEUR	
MANETTES DÉRAILLEUR	Shimano Ultegra Di2 ST-R8170
DÉRAILLEUR AVANT	Shimano Ultegra Di2 FD-R8150
DÉRAILLEUR ARRIÈRE	Shimano Ultegra Di2 RD-R8150
FREINS	Shimano Ultegra Di2 hydraulic, Shimano RT-CL800 rotors [F]160mm, [R]160mm
LEVIER DE FREIN	Shimano Ultegra Di2
CASSETTE	Shimano Ultegra, 12-speed, 11x34
CHAÎNE	Shimano Ultegra
PÉDALIER	Shimano Ultegra, 34/50 with Giant Power Pro power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
PÉDALIER	Shimano, press fit

ROUES	
JANTES	Giant SLR 0 40 Carbon Disc WheelSystem
MOYEURS	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 40T ratchet driver, CenterLock, 12mm thru-axle
RAYONS	Aero Carbon
PNEUS	CADEX Classics, tubeless, 700x32c (33.5mm), folding
EXTRAS	computer mount, fender mount, water bottle cages, tubeless prepared, 40mm max tire size
LIMITS	
MAX TIRE CLEARANCE	40mm

GÉOMÉTRIE

CADRE	XS	S	M	ML	L	XL
Longueur de tube de selle (mm)	410	445	480	515	535	565
Angle de tube de selle	74,5°	74,0°	73,5°	73,0°	73,0°	73,0°
Longueur du tube supérieur (mm)	515	530	545	560	575	595
Longueur du tube de direction (mm)	125	135	150	175	195	215
Angle du tube de direction	70,5°	71,8°	72,5°	72,5°	72,5°	72,5°
Déport de fourche (mm)	50	50	50	50	50	50
Chasse (mm)	71,6	63,4	58,6	58,6	58,6	58,6
Empattement (mm)	995	994	998	1010	1025	1040
Longueur des bases (mm)	420	420	420	420	420	420
Hauteur du boîtier de pédalier (mm)	75	75	75	70	70	70
Stack (mm)	527	541	558	577	596	615
Reach (mm)	369	375	380	384	393	402
Hauteur d'enjambement (mm)	705	733	762	796	814	841
Largeur de cintre (mm)	404	404	424	424	444	444
Longueur de potence (mm)	80	90	100	100	110	110
Longueur des manivelles (mm)	165	165	170	170	172,5	172,5

GIANT Suisse se réserve le droit de modifier les spécifications sans préavis. Photos non contractuelles.