

DEFY ADVANCED PRO 0



SPECS

CADRU	
MARIMI	XS, S, M, M/L, L, XL
CULORI	Interstellar
CADRU	Advanced-Grade Composite, 12x142mm thru-axle, disc
FURCA	Advanced SL-Grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
SOC	N/A
COMPONENTE	
GHIDON	Giant Contact SLR D-Fuse XS:40/42cm, S:40/42cm, M:42/44cm, M/L:42/44cm, L:44/46cm, XL:44/46cm
GRIPS	Stratus Lite 3.0
PIPA	Giant Contact SL AeroLight XS:80mm, S:90mm, M:100mm, M/L:100mm, L:110mm, XL:110mm
TIJA SA	Giant D-Fuse SLR, composite, -5/+15mm offset
SA	Giant Fleet SL
SISTEMUL DE SCHIMBARE A VITEZELOR	
MANETE SCHIMBATOR	Shimano Ultegra Di2 ST-R8170
SCHIMBATOR FATA	Shimano Ultegra Di2 FD-R8150
SCHIMBATOR SPATE	Shimano Ultegra Di2 RD-R8150
FRANE	Shimano Ultegra Di2 hydraulic, Shimano RT-CL800 rotors [F]160mm, [R]160mm
MANETE FRANA	Shimano Ultegra Di2
PINIOANE	Shimano Ultegra, 12-speed, 11x34
LANT	Shimano Ultegra
ANGRENAJ	Shimano Ultegra, 34/50 with Giant Power Pro power meter XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175
BOTTOM BRACKET	Shimano, press fit

ROTI	
JANTE	Giant SLR 1 36 Carbon Disc WheelSystem
BUTUCI	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 30t ratchet driver, CenterLock, 12mm thru-axle
SPITE	Sapim
ANVELOPE	CADEX Classics, tubeless, 700x32c (33.5mm), folding
EXTRAS	computer mount, fender mount, water bottle cages, tubeless prepared, 38mm max tire size
LIMITS	
MAX TIRE CLEARANCE	40mm

GEOMETRIE

CADRU	XS	S	M	ML	L	XL
Seat Tube Length (mm)	410	445	480	515	535	565
Seat Tube Angle	74,5°	74,0°	73,5°	73,0°	73,0°	73,0°
Top Tube Length (mm)	515	530	545	560	575	595
Head Tube Length (mm)	125	135	150	175	195	215
Head Tube Angle	70,5°	71,8°	72,5°	72,5°	72,5°	72,5°
Fork Rake (mm)	50	50	50	50	50	50
Trail (mm)	71,6	63,4	58,6	58,6	58,6	58,6
Wheelbase (mm)	995	994	998	1010	1025	1040
Chain Stay Length (mm)	420	420	420	420	420	420
Bottom Bracket Drop (mm)	75	75	75	70	70	70
Stack (mm)	527	541	558	577	596	615
Reach (mm)	369	375	380	384	393	402
Stand Over Height (mm)	705	733	762	796	814	841
Handlebar Width (mm)	400	400	420	420	440	440
Stem Length (mm)	80	90	100	100	110	110
Crank Length (mm)	170	170	172,5	172,5	175	175
Wheel Size	700C	700C	700C	700C	700C	700C

Toate specificatiile enumerate se pot schimba fara notificare prealabila.