



SPECIFIKACIJE

OKVIR	
VELIKOSTI	XS, S, M, M/L, L, XL
BARVE	Mariana Blue
OKVIR	Advanced-grade Composite, 12x142mm thru-axle, disc
VILICE	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
KOMPONENTE	
KRMILO	Giant Contact SLR D-Fuse XS:404/380mm, S:404/380mm, M:424/400mm, M/L:424/400mm, L:444/420mm, XL:444/420mm
GRIPS	Stratus Lite 3.0
OPORA KRMILA	Giant Contact SL AeroLight XS:80mm, S:90mm, M:100mm, M/L:100mm, L:110mm, XL:110mm
OPORA SEDEŽA	Giant D-Fuse SLR, composite, -5/+15mm offset
SEDEŽ	Giant Fleet SL
POGON	
PRESTAVNE ROČICE	Shimano Ultegra Di2 ST-R8170
PREDNJI MENJALNIK	Shimano Ultegra Di2 FD-R8150
ZADNJI MENJALNIK	Shimano Ultegra Di2 RD-R8150
ZAVORE	Shimano Ultegra Di2 hydraulic, Shimano RT-CL800 rotors [F]160mm, [R]160mm
ZAVORNE ROČICE	Shimano Ultegra Di2
VERIŽNIK	Shimano Ultegra, 12-speed, 11x34
VERIGA	Shimano Ultegra
GONILKE Z VERIŽNIKI	Shimano Ultegra, 34/50 with Giant Power Pro power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
BOTTOM BRACKET	Shimano, press fit

OBROČNIKI	
OBROČI	Giant SLR 0 40 Carbon Disc WheelSystem
PESTA	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 40T ratchet driver, CenterLock, 12mm thru-axle
NAPERE	Aero Carbon
PLAŠČI	CADEX Classics, tubeless, 700x32c (33.5mm), folding
DODATKI	computer mount, fender mount, water bottle cages, tubeless prepared, 40mm max tire size
LIMITS	
MAX TIRE CLEARANCE	40mm

GEOMETRIJA

OKVIR	XS	S	M	ML	L	XL
Dolžina sedežne cevi (mm)	410	445	480	515	535	565
Kot sedežne cevi	74,5°	74,0°	73,5°	73,0°	73,0°	73,0°
Top Tube Length (mm)	515	530	545	560	575	595
Višina glave okvirja (mm)	125	135	150	175	195	215
Krmlini kot	70,5°	71,8°	72,5°	72,5°	72,5°	72,5°
Zamik vpetja osi (mm)	50	50	50	50	50	50
Trail (mm)	71,6	63,4	58,6	58,6	58,6	58,6
Medosna razdalja (mm)	995	994	998	1010	1025	1040
Dolžina cevi ob verigi (mm)	420	420	420	420	420	420
Bottom Bracket Drop (mm)	75	75	75	70	70	70
Oddaljenost zgornje cevi od gonilne osi (mm)	527	541	558	577	596	615
Doseg (mm)	369	375	380	384	393	402
Višina zgornje cevi (mm)	705	733	762	796	814	841
Širina krmila (mm)	404	404	424	424	444	444
Dolžina opore krmila (mm)	80	90	100	100	110	110
Dolžina gonilke (mm)	165	165	170	170	172,5	172,5

Vse navedene specifikacije se lahko spremenijo brez obvestila.