

DEFY ADVANCED PRO 0

GIANT



SPECS

RAM	
STORLEKAR	XS, S, M, M/L, L, XL
FÄRGER	Mariana Blue
RAM	Advanced-grade Composite, 12x142mm thru-axle, disc
GAFFEL	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
KOMPONENTER	
STYRE	Giant Contact SLR D-Fuse XS:404/380mm, S:404/380mm, M:424/400mm, M/L:424/400mm, L:444/420mm, XL:444/420mm
GREPPAR	Stratus Lite 3.0
STAM	Giant Contact SL AeroLight XS:80mm, S:90mm, M:100mm, M/L:100mm, L:110mm, XL:110mm
SADELSTOLPE	Giant D-Fuse SLR, composite, -5/+15mm offset
SADEL	Giant Fleet SL
DRIVLINA	
VÄXLAR	Shimano Ultegra Di2 ST-R8170
FRAMVÄXEL	Shimano Ultegra Di2 FD-R8150
BAKVÄXEL	Shimano Ultegra Di2 RD-R8150
BROMSAR	Shimano Ultegra Di2 hydraulic, Shimano RT-CL800 rotors [F]160mm, [R]160mm
BROMSSPAKAR	Shimano Ultegra Di2
KASSETT	Shimano Ultegra, 12-speed, 11x34
KEDJA	Shimano Ultegra
VEVPARTI	Shimano Ultegra, 34/50 with Giant Power Pro power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
BROMSREGLAGE	Shimano, press fit

HJUL	
FÄLGAR	Giant SLR 0 40 Carbon Disc WheelSystem
NAV	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 40T ratchet driver, CenterLock, 12mm thru-axle
EKRAR	Aero Carbon
DÄCK	CADEX Classics, tubeless, 700x32c (33.5mm), folding
EXTRAFUNKTIONER	computer mount, fender mount, water bottle cages, tubeless prepared, 40mm max tire size
GRÄNSER	
MAX DÄCKAVSTÅND	40mm

Price: 79 990,00 kr

GEOMETRY

RAM	S	M	ML	L	XL
Längd sadelrör (mm)	445	480	515	535	565
Vinkel sadelrör	74,0°	73,5°	73,0°	73,0°	73,0°
Topprörets längd (mm)	530	545	560	575	595
Styrhuvud Längd (mm)	135	150	175	195	215
Vinkel styrhuvud	71,8°	72,5°	72,5°	72,5°	72,5°
Gaffelvinkel (mm)	50	50	50	50	50
Spår (mm)	63,4	58,6	58,6	58,6	58,6
Hjulbas (mm)	994	998	1010	1025	1040
Kedjestagslängd (mm)	420	420	420	420	420
Nedre fäste Drop (mm)	75	75	70	70	70
Stack (mm)	541	558	577	596	615
Reach (mm)	375	380	384	393	402
Stå över höjden (mm)	733	762	796	814	841
Styrets bredd (mm)	404	424	424	444	444
Stamlängd (mm)	90	100	100	110	110
Vevlängd (mm)	165	170	170	172,5	172,5

All specifications listed are subject to change without notice.