

DEFY ADVANCED PRO 0



產品規格

車架	
尺寸	XS, S, M, M/L, L, XL
顏色	Interstellar
車架	Advanced-Grade Composite, 12x142mm thru-axle, disc
前叉	Advanced SL-Grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
避震器	N/A
COMPONENTS	
車把手	Giant Contact SLR D-Fuse XS:40/42cm, S:40/42cm, M:42/44cm, M/L:42/44cm, L:44/46cm, XL:44/46cm
把手帶/套	Stratus Lite 3.0
豎桿	Giant Contact SL AeroLight XS:80mm, S:90mm, M:100mm, M/L:100mm, L:110mm, XL:110mm
座桿	Giant D-Fuse SLR, composite, -5/+15mm offset
坐墊	Giant Fleet SL
DRIVETRAIN	
變速把手	Shimano Ultegra Di2 ST-R8170
前變速器	Shimano Ultegra Di2 FD-R8150
後變速器	Shimano Ultegra Di2 RD-R8150
煞車系統	Shimano Ultegra Di2 hydraulic, Shimano RT-CL800 rotors [F]160mm, [R]160mm
煞車把手	Shimano Ultegra Di2
飛輪	Shimano Ultegra, 12-speed, 11x34
鍊條	Shimano Ultegra
大齒盤	Shimano Ultegra, 34/50 with Giant Power Pro power meter XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175
BOTTOM BRACKET (B B)	Shimano, press fit

輪組	
輪圈	Giant SLR 1 36 Carbon Disc WheelSystem
花鼓	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 30t ratchet driver, CenterLock, 12mm thru-axle
輻條	Sapim
外胎	CADEX Classics, tubeless, 700x32c (33.5mm), folding
其他	computer mount, fender mount, water bottle cages, tubeless prepared, 38mm max tire size
LIMITS	
MAX TIRE CLEARANCE	40mm

Price: NT\$158,000

車架幾何

車架	XS	S	M	ML
座(立)管長 (mm)	410	445	480	515
座(立)管角度	74.5°	74.0°	73.5°	73.0°
上管長度 (mm)	515	530	545	560
頭管長度 (mm)	125	135	150	175
頭管角度	70.5°	71.8°	72.5°	72.5°
前叉 (mm)	50	50	50	50
Trail (mm)	71.6	63.4	58.6	58.6
前後輪距 (mm)	995	994	998	1010
後下叉長度 (mm)	420	420	420	420
五通下降高度 (mm)	75	75	75	70
頭碗至五通高度 (mm)	527	541	558	577
頭碗至五通長度 (mm)	369	375	380	384
上管至地面高度 (mm)	705	733	762	796
把手寬 (mm)	400	400	420	420
龍頭長度 (mm)	80	90	100	100
曲柄長度 (mm)	170	170	172.5	172.5
輪組尺寸	700C	700C	700C	700C

* 捷安特公司對本網站所刊載之產品資料保留修改權利，恕不另行通知(包括有關設備、規格、型號、重量、顏色和材料等)，請以實際產品為主。