

DEFY ADVANCED PRO 1

GIANT



SPECIFIKATIONER

RAMME	
STØRRELSER	S, M, M/L, L, XL
FARVER	Meteor Storm
RAMME	Advanced-Grade Composite, 12x142mm thru-axle, disc
FORGAFFEL	Advanced SL-Grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
KOMPONENTER	
STYR	Giant Contact SL D-Fuse XS:40/42cm, S:40/42cm, M:42/44cm, M/L:42/44cm, L:44/46cm, XL:44/46cm
GREB / STYRBÅND	Stratus Lite 3.0
FREMPIND	Giant Contact SL AeroLight XS:80mm, S:90mm, M:100mm, M/L:100mm, L:110mm, XL:110mm
SADELPIND	Giant D-Fuse SL, composite, -5/+15mm offset
SADEL	Giant Fleet SL
GEARGRUPPE	
SKIFTEGREB	SRAM Rival eTap AXS
FORSKIFTER	SRAM Rival eTap AXS
BAGSKIFTER	SRAM Rival eTap AXS
BREMSE	SRAM Rival eTap AXS hydraulic, SRAM PaceLine rotors [F]160mm, [R]140mm
BREMSEGREB	SRAM Rival eTap AXS hydraulic
KASSETTE	SRAM Rival, 12-speed, 10x36
KÆDE	SRAM Rival D1
KRANKSÆT	SRAM Rival D1 DUB, 33/46 with Giant Power Halo power meter XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
KRANKBOKS	SRAM DUB, press fit

HJUL	
FÆLGE	Giant SLR 1 36 Carbon Disc WheelSystem
NAV	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 30t ratchet driver, CenterLock, 12mm thru-axle
EGER	Sapim
DÆK	Giant Gavia Fondo 1, tubeless, 700x32c (33.5mm), folding
EKSTRA	computer mount, fender mount, water bottle cages, tubeless prepared, 38mm max tire size
GRÆNSER	
MAX DÆKSTØRRELSE	40mm

Pris: 39.999,00 kr.

GEOMETRI

RAMME	S	M	ML	L	XL
Sadelrørslængde (mm)	445	480	515	535	565
Sadelrørsvinkel	74,0°	73,5°	73,0°	73,0°	73,0°
Overrørslængde (mm)	530	545	560	575	595
Kronrørslængde (mm)	135	150	175	195	215
Kronrørsvinkel	71,8°	72,5°	72,5°	72,5°	72,5°
Forgaffel fremspring (rake) (mm)	50	50	50	50	50
Sti (mm)	63,4	58,6	58,6	58,6	58,6
Akselafstand (mm)	994	998	1010	1025	1040
Kædestagslængde (mm)	420	420	420	420	420
Krankboks drop (mm)	75	75	70	70	70
Stack (mm)	541	558	577	596	615
Reach (mm)	375	380	384	393	402
Skridthøjde (mm)	733	762	796	814	841
Styrbredde (mm)	400	420	420	440	440
Frempindslængde (mm)	90	100	100	110	110
Pedalarmslængde (mm)	170	172,5	172,5	175	175
Hjulstørrelse	700C	700C	700C	700C	700C

Alle de anførte specifikationer kan ændres uden varsel.