

DEFY ADVANCED PRO 1

GIANT



SPECIFIKATIONER

RAMME	
STØRRELSER	S, M, M/L, L, XL
FARVER	White/Iris
RAMME	Advanced-grade Composite, 12x142mm thru-axle, disc
FORGAFFEL	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
BAGDÆMPER	N/A
KOMponenter	
STYR	Giant Contact SLR D-Fuse XS:404/380mm, S:404/380mm, M:424/400mm, M/L:424/400mm, L:444/420mm, XL:444/420mm
GREB / STYRBÅND	Stratus Lite 3.0
FREMPIND	Giant Contact SL AeroLight XS:80mm, S:90mm, M:100mm, M/L:100mm, L:110mm, XL:110mm
SADELPIND	Giant D-Fuse SL, composite, -5/+15mm offset
SADEL	Giant Fleet SL
GEARGRUPPE	
SKIFTEGREB	SRAM Rival AXS E1
FORSKIFTER	SRAM Rival AXS E1
BAGSKIFTER	SRAM Rival AXS E1
BREMSER	SRAM Rival AXS E1 hydraulic, SRAM PaceLine rotors [F]160mm, [R]160mm
BREMSEGREB	SRAM Rival AXS E1 hydraulic
KASSETTE	SRAM Rival, 12-speed, 10x36
KÆDE	SRAM Rival E1
KRANKSÆT	SRAM Rival E1 DUB, 33/46 with Quark power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
KRANKBOKS	SRAM DUB, press fit

HJUL	
FÆLGE	Giant SLR 1 40 Carbon Disc WheelSystem
NAV	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 30T ratchet driver, CenterLock, 12mm thru-axle
EGER	Sapim
DÆK	Giant Gavia Fondo 0, tubeless, 700x32c (33.5mm), folding
EKSTRA	computer mount, fender mount, water bottle cages, tubeless prepared, 40mm max tire size
GRÆNSER	
MAX DÆKSTØRRELSE	40mm

Pris: 40.999,00 kr.

GEOMETRI

RAMME	S	M	ML	L	XL
Sadelrørs længde (mm)	445	480	515	535	565
Sadelrørs vinkel	74,0°	73,5°	73,0°	73,0°	73,0°
Overrørs længde (mm)	530	545	560	575	595
Kronrørs længde (mm)	135	150	175	195	215
Kronrørs vinkel	71,8°	72,5°	72,5°	72,5°	72,5°
Forgaffel fremspring (rake) (mm)	50	50	50	50	50
Sti (mm)	63,4	58,6	58,6	58,6	58,6
Akselafstand (mm)	994	998	1010	1025	1040
Kædestags længde (mm)	420	420	420	420	420
Krankboks drop (mm)	75	75	70	70	70
Stack (mm)	541	558	577	596	615
Reach (mm)	375	380	384	393	402
Skridthøjde (mm)	733	762	796	814	841
Styrbredde (mm)	404	424	424	444	444
Frempindslængde (mm)	90	100	100	110	110
Pedalarmslængde (mm)	165	170	170	172,5	172,5

Alle de anførte specifikationer kan ændres uden varsel.