

DEFY ADVANCED PRO 1



SPEZIFIKATIONEN

RAHMEN & GABEL	
RAHMENGRÖSSEN	XS, S, M, M/L, L, XL
FARBE(N)	Midnight Moon
RAHMEN	Advanced-grade Composite, 12x142mm thru-axle, disc
GABEL	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
COCKPIT	
LENKER	Giant Contact SL D-Fuse XS:410/380mm, S:410/380mm, M:430/400mm, M/L:430/400mm, L:450/420mm, XL:450/420mm
GRIFFE	Stratus Lite 3.0
VORBAU	Giant Contact SL AeroLight XS:80mm, S:90mm, M:100mm, M/L:100mm, L:110mm, XL:110mm
SATTELSTÜTZE	Giant D-Fuse SL, composite, 16mm offset
SATTEL	Giant Fleet SL
SCHALTUNG, ANTRIEB	
SCHALTHEBEL	SRAM Rival AXS E1
UMWERFER	SRAM Rival AXS E1
SCHALTWERK	SRAM Rival AXS E1
BREMSEN	SRAM Rival AXS E1 hydraulic, SRAM PaceLine rotors [F]160mm, [R]160mm
BREMSEHEBEL	SRAM Rival AXS E1 hydraulic
KASSETTE	SRAM Rival, 12-speed, 10x36
KETTE	SRAM Rival E1
KURBELSATZ	SRAM Rival E1 DUB, 33/46 with power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
INNENLAGER	SRAM DUB, press fit

LAUFRÄDER	
FELGEN	Giant SLR 1 40 Carbon Disc WheelSystem
NABEN (V/H)	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 30T ratchet driver, CenterLock, 12mm thru-axle
SPEICHEN	Sapim
REIFEN	Giant Gavia Fondo 0, tubeless, 700x32c (33.5mm), folding
ZUBEHÖR (TEILW. VERBAUT)	computer mount, fender mount, water bottle cages, tubeless prepared
GRENZEN	
MAX. REIFENBREITE	40mm

UVP: 5.000,00 €

GEOMETRIEDATEN

RAHMEN & GABEL	S	M	ML	L	XL
Sitzrohrlänge (mm)	445	480	515	535	565
Einstecktiefe der Sattelstütze (mm)	190	190	190	190	190
Sitzwinkel	74,0°	73,5°	73,0°	73,0°	73,0°
Oberrohrlänge (mm)	530	545	560	575	595
Steuerrohrlänge (mm)	135	150	175	195	215
Lenkwinkel	71,8°	72,5°	72,5°	72,5°	72,5°
Gabelvorbiegung (mm)	50	50	50	50	50
Gabelnachlauf (mm)	63,4	58,6	58,6	58,6	58,6
Radstand (mm)	994	998	1010	1025	1040
Kettenstrebienlänge (mm)	420	420	420	420	420
Tretlagerabsenkung (mm)	75	75	70	70	70
Stack (mm)	541	558	577	596	615
Reach (mm)	375	380	384	393	402
Überstands-/Durchstiegshöhe (mm)	733	762	796	814	841
Lenkerbreite (mm)	404	424	424	444	444
Vorbaulänge (mm)	90	100	100	110	110
Kurbelarmlänge (mm)	165	170	170	172,5	172,5

Spezifikations-, Preis- und Farbänderungen vorbehalten.