



SPECS

FRAME	
SIZES	XS, S, M, M/L, L, XL
COLOURS	White/Iris
FRAME	Advanced-grade Composite, 12x142mm thru-axle, disc
FORK	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Contact SLR D-Fuse XS:404/380mm, S:404/380mm, M:424/400mm, M/L:424/400mm, L:444/420mm, XL:444/420mm
GRIPS	Stratus Lite 3.0
STEM	Giant Contact SL AeroLight XS:80mm, S:90mm, M:100mm, M/L:100mm, L:110mm, XL:110mm
SEATPOST	Giant D-Fuse SL, composite, -5/+15mm offset
SADDLE	Giant Fleet SL
DRIVETRAIN	
SHIFTERS	SRAM Rival AXS E1
FRONT DERAILLEUR	SRAM Rival AXS E1
REAR DERAILLEUR	SRAM Rival AXS E1
BRAKES	SRAM Rival AXS E1 hydraulic, SRAM PaceLine rotors [F]160mm, [R]160mm
BRAKE LEVERS	SRAM Rival AXS E1 hydraulic
CASSETTE	SRAM Rival, 12-speed, 10x36
CHAIN	SRAM Rival E1
CRANKSET	SRAM Rival E1 DUB, 33/46 with power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant SLR 1 40 Carbon Disc WheelSystem
HUBS	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 30T ratchet driver, CenterLock, 12mm thru-axle
SPOKES	Sapim
TIRES	Giant Gavia Fondo 0, tubeless, 700x32c (33.5mm), folding
EXTRAS	computer mount, fender mount, water bottle cages, tubeless prepared, 40mm max tire size
LIMITS	
MAX TIRE CLEARANCE	40mm

Suggested Retail Price (CDN): \$6,699.00

FRAME GEOMETRY

FRAME	XS	S	M	ML	L	XL
Seat Tube Length (mm)	410	445	480	515	535	565
Seat Tube Angle	74.5°	74.0°	73.5°	73.0°	73.0°	73.0°
Top Tube Length (mm)	515	530	545	560	575	595
Head Tube Length (mm)	125	135	150	175	195	215
Head Tube Angle	70.5°	71.8°	72.5°	72.5°	72.5°	72.5°
Fork Rake (mm)	50	50	50	50	50	50
Trail (mm)	71.6	63.4	58.6	58.6	58.6	58.6
Wheelbase (mm)	995	994	998	1010	1025	1040
Chain Stay Length (mm)	420	420	420	420	420	420
Bottom Bracket Drop (mm)	75	75	75	70	70	70
Stack (mm)	527	541	558	577	596	615
Reach (mm)	369	375	380	384	393	402
Stand Over Height (mm)	705	733	762	796	814	841
Handlebar Width (mm)	404	404	424	424	444	444
Stem Length (mm)	80	90	100	100	110	110
Crank Length (mm)	165	165	170	170	172.5	172.5

All prices and specifications are subject to change without notice.