

# DEFY ADVANCED PRO 1



## SPECS

| FRAME                   |  |
|-------------------------|--|
| <b>SIZES</b>            | XS, S, M, M/L, L, XL   |
| <b>COLOURS</b>          | White/Iris   |
| <b>FRAME</b>            | Advanced-grade Composite, 12x142mm thru-axle, disc   |
| <b>FORK</b>             | Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc                 |
| <b>SHOCK</b>            | N/A  |
| COMPONENTS              |  |
| <b>HANDLEBAR</b>        | Giant Contact SL D-Fuse S:404/380mm, M:424/400mm, M/L:424/400mm, L:444/420mm, XL:444/420mm                   |
| <b>GRIPS</b>            | Stratus Lite 3.0   |
| <b>STEM</b>             | Giant Contact SL AeroLight XS:80mm, S:90mm, M:100mm, M/L:100mm, L:110mm, XL:110mm                            |
| <b>SEATPOST</b>         | Giant D-Fuse SL, composite, -5/+15mm offset  |
| <b>SADDLE</b>           | Giant Fleet SL   |
| DRIVETRAIN              |  |
| <b>SHIFTERS</b>         | SRAM Rival AXS E1  |
| <b>FRONT DERAILLEUR</b> | SRAM Rival AXS E1  |
| <b>REAR DERAILLEUR</b>  | SRAM Rival AXS E1  |
| <b>BRAKES</b>           | SRAM Rival AXS E1 hydraulic, SRAM PaceLine rotors [F]160mm, [R]160mm   |
| <b>BRAKE LEVERS</b>     | SRAM Rival AXS E1 hydraulic  |
| <b>CASSETTE</b>         | SRAM Rival, 12-speed, 10x36  |
| <b>CHAIN</b>            | SRAM Rival E1  |
| <b>CRANKSET</b>         | SRAM Rival E1 DUB, 33/46 with Quark power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm |
| <b>BOTTOM BRACKET</b>   | SRAM DUB, press fit  |

| WHEELS                    |  |
|---------------------------|--|
| <b>RIMS</b>               | Giant SLR 1 40 Carbon Disc WheelSystem   |
| <b>HUBS</b>               | [F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 30T ratchet driver, CenterLock, 12mm thru-axle |
| <b>SPOKES</b>             | Sapim  |
| <b>TYRES</b>              | Giant Gavia Fondo 0, tubeless, 700x32c (33.5mm), folding   |
| <b>EXTRAS</b>             | computer mount, fender mount, water bottle cages, tubeless prepared, 40mm max tire size  |
| LIMITS                    |  |
| <b>MAX TIRE CLEARANCE</b> | 40mm   |

**Price: €4,999.00**

## GEOMETRY

| FRAME                    | S     | M     | ML    | L     | XL    |
|--------------------------|-------|-------|-------|-------|-------|
| Seat Tube Length (mm)    | 445   | 480   | 515   | 535   | 565   |
| Seat Tube Angle          | 74.0° | 73.5° | 73.0° | 73.0° | 73.0° |
| Top Tube Length (mm)     | 530   | 545   | 560   | 575   | 595   |
| Head Tube Length (mm)    | 135   | 150   | 175   | 195   | 215   |
| Head Tube Angle          | 71.8° | 72.5° | 72.5° | 72.5° | 72.5° |
| Fork Rake (mm)           | 50    | 50    | 50    | 50    | 50    |
| Trail (mm)               | 63.4  | 58.6  | 58.6  | 58.6  | 58.6  |
| Wheelbase (mm)           | 994   | 998   | 1010  | 1025  | 1040  |
| Chain Stay Length (mm)   | 420   | 420   | 420   | 420   | 420   |
| Bottom Bracket Drop (mm) | 75    | 75    | 70    | 70    | 70    |
| Stack (mm)               | 541   | 558   | 577   | 596   | 615   |
| Reach (mm)               | 375   | 380   | 384   | 393   | 402   |
| Stand Over Height (mm)   | 733   | 762   | 796   | 814   | 841   |
| Handlebar Width (mm)     | 404   | 424   | 424   | 444   | 444   |
| Stem Length (mm)         | 90    | 100   | 100   | 110   | 110   |
| Crank Length (mm)        | 165   | 170   | 170   | 172.5 | 172.5 |

*All specifications listed are subject to change without notice.*